

Declaration of Performance for the construction product Sto-Fossil Bavaria Creme (NSF014)

Unique identification code of the product-type	PROD3855 Sto-Fossil Bavaria Creme (NSF014)
Intended use/es	natural stone cladding board for wall and ceiling cladding in interiors and exteriors
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	CWFT (reaction to fire) System 3 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 1469:2015
Notified body/ies	0780
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 1469:2015
Water absorption	NPD	EN 1469:2015
Water vapour permeability	NPD	EN 1469:2015
Durability	10.0 MPa without freeze-thaw cycle (average value)	EN 1469:2015
Durability	9.0 MPa after 56 days freeze-thaw cycle (average value)	EN 1469:2015
Dangerous substances	NPD	EN 1469:2015
Flexural strength	7,0 MPa (lower expected value)	EN 1469:2015
Flexural strength	10,0 MPa (mean expected value)	EN 1469:2015
Capillary absorption	NPD	EN 1469:2015
Bulk density	NPD	EN 1469:2015
Apparent porosity	NPD	EN 1469:2015
Breaking load at the dowel hole	1,000 N (d1 = 10 mm) (lower expected value)	EN 1469:2015
Breaking load at the dowel hole	1,500 N (d1 = 10 mm) (mean expected value)	EN 1469:2015
Breaking load at the dowel hole	490 N (d1 = 10 mm) (standard deviation)	EN 1469:2015
Resistance to thermal shock	NPD	EN 1469:2015
Petrographic description	NPD	EN 1469:2015

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

16.12.2025

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstr. 1
D-79780 Stühlingen

0101-0295-3

17

0780

PROD3855 Sto-Fossil Bavaria Creme (NSF014)
EN 1469:2015 natural stone cladding board

for wall and ceiling cladding in interiors and exteriors

Reaction to fire	A1
Water absorption	NPD
Durability	10.0 MPa without freeze-thaw cycle (average value)
Durability	9.0 MPa after 56 days freeze-thaw cycle (average value)
Flexural strength	7,0 MPa (lower expected value)
Flexural strength	10,0 MPa (mean expected value)
Water vapour permeability	NPD
Dangerous substances	NPD
Capillary absorption	NPD
Apparent porosity	NPD
Breaking load at the dowel hole	1,000 N (d1 = 10 mm) (lower expected value)
Breaking load at the dowel hole	1,500 N (d1 = 10 mm) (mean expected value)
Breaking load at the dowel hole	490 N (d1 = 10 mm) (standard deviation)
Resistance to thermal shock	NPD
Petrographic description	NPD