

# Declaration of Performance for the construction product Sto-Fossil Bavaria Yellow (NSF001)

<b>Unique identification code of the product-type</b>	PROD3847 Sto-Fossil Bavaria Yellow (NSF001)
<b>Intended use/es</b>	natural stone cladding board for wall and ceiling cladding in interiors and exteriors
<b>Manufacturer</b>	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
<b>System/s of AVCP</b>	CWFT (reaction to fire) System 3 (applies to all other "Essential characteristics" in the table)
<b>Harmonised standard</b>	EN 1469:2015
<b>Notified body/ies</b>	0780
<b>European Assessment Document</b>	Not relevant
<b>European Technical Assessment</b>	Not relevant
<b>Technical Assessment Body</b>	Not relevant
<b>Appropriate Technical Documentation and/or Specific Technical Documentation</b>	Not relevant

## Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 1469:2015
Water absorption	NPD	EN 1469:2015
Water vapour permeability	NPD	EN 1469:2015
Durability	13.5 MPa without freeze-thaw cycle (average value)	EN 1469:2015
Durability	12.5 MPa after 56 days freeze-thaw cycle (average value)	EN 1469:2015
Dangerous substances	NPD	EN 1469:2015
Flexural strength	10,2 MPa (lower expected value)	EN 1469:2015
Flexural strength	13,5 MPa (mean expected value)	EN 1469:2015
Capillary absorption	NPD	EN 1469:2015
Bulk density	NPD	EN 1469:2015
Apparent porosity	NPD	EN 1469:2015
Breaking load at the dowel hole	1,100 N (d1 = 10 mm) (lower expected value)	EN 1469:2015
Breaking load at the dowel hole	1,700 N (d1 = 10 mm) (mean expected value)	EN 1469:2015
Breaking load at the dowel hole	450 N (d1 = 10 mm) (standard deviation)	EN 1469:2015
Resistance to thermal shock	NPD	EN 1469:2015
Petrographic description	NPD	EN 1469:2015

*NPD = no performance determined*

---

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

**16.12.2025**

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at [www.sto.com/ce](http://www.sto.com/ce).



Sto SE & Co. KGaA  
Ehrenbachstr. 1  
D-79780 Stühlingen

0101-0290-3

17

0780

**PROD3847 Sto-Fossil Bavaria Yellow (NSF001)**  
**EN 1469:2015 natural stone cladding board**

for wall and ceiling cladding in interiors and exteriors

Reaction to fire	A1
Water absorption	NPD
Durability	13.5 MPa without freeze-thaw cycle (average value)
Durability	12.5 MPa after 56 days freeze-thaw cycle (average value)
Flexural strength	10,2 MPa (lower expected value)
Flexural strength	13,5 MPa (mean expected value)
Water vapour permeability	NPD
Dangerous substances	NPD
Capillary absorption	NPD
Apparent porosity	NPD
Breaking load at the dowel hole	1,100 N (d1 = 10 mm) (lower expected value)
Breaking load at the dowel hole	1,700 N (d1 = 10 mm) (mean expected value)
Breaking load at the dowel hole	450 N (d1 = 10 mm) (standard deviation)
Resistance to thermal shock	NPD
Petrographic description	NPD