

Declaration of Performance for the construction product Sto-Fossil SKL (NSF004)

Unique identification code of the product-type	PROD3850 Sto-Fossil SKL (NSF004)
Intended use/es	for wall and ceiling cladding in interiors and exteriors
Manufacturer	VeroStone GmbH, Mergentheimer Straße, D-97268 Kirchheim
System/s of AVCP	System 3 (reaction to fire) System 4 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 12057:2004
Notified body/ies	BPS Wismar GmbH NB 0943
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 12057:2004
Water vapour permeability	NPD	EN 12057:2004
Durability	6.8 MPa without freeze-thaw cycle (average value)	EN 12057:2004
Durability	6.8 MPa after 14 freeze-thaw cycles (average value)	EN 12057:2004
Durability	7.7 MPa after 56 freeze-thaw cycles (average value)	EN 12057:2004
Dangerous substances	NPD	EN 12057:2004
Thermal resistance	NPD	EN 12057:2004
Bending strength	6.37 MPa (lower expected value)	EN 12057:2004
Bulk density	2,46 g/cm ³ (average value)	EN 12057:2004
Apparent porosity	8,0 % (average value)	EN 12057:2004
Resistance to thermal shock	NPD	EN 12057:2004
Radioactive emission	NPD	EN 12057:2004
Direct airborne sound insulation	NPD	EN 12057:2004
Resistance of marble when subject to cyclic stress from heat and moisture	NPD	EN 12057:2004

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

15.11.2023

VeroStone GmbH, Mergentheimer Straße, D-97268 Kirchheim

The current valid version of the declaration of performance is available at www.sto.com/ce.



VeroStone GmbH
Mergentheimer Straße
D-97268 Kirchheim

0101-0294-2

17

NB 0943

PROD3850 Sto-Fossil SKL (NSF004)

for wall and ceiling cladding in interiors and exteriors

Reaction to fire	A1
Durability	6.8 MPa without freeze-thaw cycle (average value)
Durability	6.8 MPa after 14 freeze-thaw cycles (average value)
Durability	7.7 MPa after 56 freeze-thaw cycles (average value)
Water vapour permeability	NPD
Dangerous substances	NPD
Thermal resistance	NPD
Bending strength	6.37 MPa (lower expected value)
Bulk density	2,46 g/cm ³ (average value)
Apparent porosity	8,0 % (average value)
Resistance to thermal shock	NPD
Radioactive emission	NPD
Direct airborne sound insulation	NPD
Resistance of marble when subject to cyclic stress from heat and moisture	NPD