

Declaration of Performance for the construction product

Sto-Gabbro Nero Transvaal (NSF012)



Unique identification code of the product-type	PROD4085 Sto-Gabbro Nero Transvaal (NSF012)
Intended use/es	general purpose plastering mortar - base coat CS II for wall and ceiling cladding in interiors and exteriors
Manufacturer	VeroStone GmbH, Willibaldstr. 38, D-85072 Eichstätt-Blumenberg
System/s of AVCP	System 4 (reaction to fire) System 4 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 12057:2015
Notified body/ies	Not relevant
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s		
Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 12057:2015
Water absorption	0.3 M % (average value)	EN 12057:2015
Water vapour permeability	NPD	EN 12057:2015
Durability	19.4 MPa without freeze-thaw cycle (average value)	EN 12057:2015
Durability	17.1 MPa after 12 freeze-thaw cycles (average value)	EN 12057:2015
Dangerous substances	NPD	EN 12057:2015
Bending strength	19.4 MPa (lower expected value)	EN 12057:2015
Bulk density	2,95 g/cm ³	EN 12057:2015
Apparent porosity	0,14 %	EN 12057:2015
Resistance to thermal shock	NPD	EN 12057:2015
Petrographic description	Gabbro	EN 12057:2015
Radioactive emission	NPD	EN 12057:2015

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

15.07.2022

Sto SE & Co. KGaA D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstraße 1
D-79780 Stühlingen

0101-0307-1

18

PROD4085 Sto-Gabbro Nero Transvaal (NSF012)
EN 12057:2015 general purpose plastering mortar - base coat CS II
for wall and ceiling cladding in interiors and exteriors

Reaction to fire	A1
Water absorption	0.3 M % (average value)
Durability	19.4 MPa without freeze-thaw cycle (average value)
Durability	17.1 MPa after 12 freeze-thaw cycles (average value)
Water vapour permeability	NPD
Dangerous substances	NPD
Bending strength	19.4 MPa (lower expected value)
Bulk density	2,95 g/cm ³
Apparent porosity	0,14 %
Resistance to thermal shock	NPD
Petrographic description	Gabbro
Radioactive emission	NPD