

Declaration of Performance for the construction product

Sto-Joint Filler WF

Unique identification code of the product-type	PROD0125 Sto-Joint Filler WF
Intended use/es	joint sealant for facade elements joint sealant for use in interiors, type F-INT conditioning: method B, carrier material: mortar M 2
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 3 (reaction to fire) System 3 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 15651-1:2012
Notified body/ies	Not relevant
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	E	EN 15651-1:2012
Durability	pass	EN 15651-1:2012
Resistance to flow	≤ 5 mm	EN 15651-1:2012
Volume loss	≤ 45 %	EN 15651-1:2012
Tensile behaviour / expansion behaviour after immersion in water (malleable)	≥ 25 % (At 23 °C)	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	EN 15651-1:2012

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

17.05.2023

Sto SE & Co. KGaA D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstraße 1
D-79780 Stühlingen

0101-0227-2

14

PROD0125 Sto-Joint Filler WF
EN 15651-1:2012 joint sealant for facade elements

joint sealant for use in interiors, type F-INT
conditioning: method B, carrier material: mortar M 2

Reaction to fire	E
Durability	pass
Resistance to flow	≤ 5 mm
Volume loss	≤ 45 %
Tensile behaviour / expansion behaviour after immersion in water (malleable)	≥ 25 % (At 23 °C)
Release of chemicals dangerous to the environment and health	NPD