

# Declaration of Performance for the construction product StoBrick 100-999

<b>Unique identification code of the product-type</b>	PROD5094 StoBrick 100-999
<b>Intended use/es</b>	ceramic tiles for cladding walls in interiors and exteriors
<b>Manufacturer</b>	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
<b>System/s of AVCP</b>	System 4 (reaction to fire) System 4 (applies to all other "Essential characteristics" in the table)
<b>Harmonised standard</b>	EN 14411:2012
<b>Notified body/ies</b>	Not relevant
<b>European Assessment Document</b>	Not relevant
<b>European Technical Assessment</b>	Not relevant
<b>Technical Assessment Body</b>	Not relevant
<b>Appropriate Technical Documentation and/or Specific Technical Documentation</b>	Not relevant

## Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 14411:2012
Durability	pass for uses in interiors	EN 14411:2012
Durability	pass for uses in exteriors: resistance to freeze-thaw cycles	EN 14411:2012
Bond strength	≥ 0,5 N/mm <sup>2</sup> Cementitious adhesives, type C1	EN 14411:2012
Resistance to thermal shock	pass	EN 14411:2012

*NPD = no performance determined*

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

23.01.2025

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at [www.sto.com/ce](http://www.sto.com/ce).



Sto SE & Co. KGaA  
Ehrenbachstr. 1  
D-79780 Stühlingen

**0101-0443-1**

**25**

**PROD5094 StoBrick 100-999**  
**EN 14411:2012 ceramic tiles**

for cladding walls in interiors and exteriors

Reaction to fire	A1
Durability	pass for uses in interiors
Durability	pass for uses in exteriors: resistance to freeze-thaw cycles
Bond strength	≥ 0,5 N/mm <sup>2</sup> Cementitious adhesives, type C1
Resistance to thermal shock	pass