

Declaration of Performance for the construction product StoBrick 2000

Unique identification code of the product-type	PROD3261 StoBrick 2000
Intended use/es	U brick for use in unprotected masonry, category I
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	system 2+ (reaction to fire) system 2+ (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 771-1:2011 + A1:2015
Notified body/ies	CERT Baustoffe GmbH 2510
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 771-1:2011 + A1:2015
Water absorption	≤ 15 [Masse-%]	EN 771-1:2011 + A1:2015
Water vapour permeability	NPD	EN 771-1:2011 + A1:2015
Dangerous substances	NPD	EN 771-1:2011 + A1:2015
Thermal resistance	NPD	EN 771-1:2011 + A1:2015
Frost resistance	NPD	EN 771-1:2011 + A1:2015
Compressive strength	Category I masonry unit	EN 771-1:2011 + A1:2015
Bond strength	NPD	EN 771-1:2011 + A1:2015
Shape and formation	Brick slips	EN 771-1:2011 + A1:2015
Dimensional stability	NPD	EN 771-1:2011 + A1:2015
Airborne sound insulation	NPD	EN 771-1:2011 + A1:2015
Dimensions	210/22/65 (length/width/height) [mm]	EN 771-5:2011 + A1:2015
Limit deviations	Tm +-4, +-2, +-3 (average value)	EN 771-5:2011 + A1:2015
Dimension range	Rm 5, 3, 3	EN 771-5:2011 + A1:2015
Active soluble salt content	Class S2	EN 771-5:2011 + A1:2015
Net dry bulk density	NPD	EN 771-5:2011 + A1:2015

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

24.03.2026

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstr. 1
D-79780 Stühlingen

0101-0314-3

19

2510

PROD3261 StoBrick 2000
EN 771-1:2011 + A1:2015 U brick for use in unprotected masonry, category I

Reaction to fire	A1
Water absorption	≤ 15 [Masse-%]
Water vapour permeability	NPD
Dangerous substances	NPD
Thermal resistance	NPD
Frost resistance	NPD
Compressive strength	Category I masonry unit
Bond strength	NPD
Shape and formation	Brick slips
Dimensional stability	NPD
Airborne sound insulation	NPD
Dimensions	210/22/65 (length/width/height) [mm]
Limit deviations	Tm +4, +-2, +-3 (average value)
Dimension range	Rm 5, 3, 3
Active soluble salt content	Class S2
Net dry bulk density	NPD