Declaration of Performance for the construction product

StoBrick 3000

Unique identification code of the product-type	PROD4091 StoBrick 3000
Intended use/es	ceramic tiles for cladding walls in interiors and exteriors
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 4 (reaction to fire) System 4 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 14411:2012
Notified body/ies	NPD
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 14411:2012
Durability	pass for uses in interiors	EN 14411:2012
Durability	pass for uses in exteriors: resistance to freeze-thaw cycles	EN 14411:2012
Bond strength	≥ 0,5 N/mm² Cementitious adhesives, type C1	EN 14411:2012
Resistance to thermal shock	pass	EN 14411:2012
Cadmium release	NPD	EN 14411:2012
Lead release	NPD	EN 14411:2012

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

14.03.2023

Sto SE & Co. KGaA D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.

Sto SE & Co. KGaA

Ehrenbachstraße 1

D-79780 Stühlingen

0101-0309-2 **18**

PROD4091 StoBrick 3000
EN 14411:2012 ceramic tiles

for cladding walls in interiors and exteriors

Reaction to fire	A1
Durability	pass for uses in interiors
Durability	pass for uses in exteriors: resistance to freeze-thaw cycles
Bond strength	≥ 0,5 N/mm² Cementitious adhesives, type C1
Resistance to thermal shock	pass
Cadmium release	NPD
Lead release	NPD