

# Declaration of Performance for the construction product

## StoBrick 4000

**Unique identification code of the product-type** PRODS026 StoBrick 4000

**Intended use/es** ceramic tiles  
for cladding walls in interiors and exteriors

**Manufacturer**

**System/s of AVCP** System 4 (reaction to fire)  
System 4 (applies to all other "Essential characteristics" in the table)

**Harmonised standard** EN 14411:2012

**Notified body/ies** NPD

**European Assessment Document** Not relevant

**European Technical Assessment** Not relevant

**Technical Assessment Body** Not relevant

**Appropriate Technical Documentation and/or Specific Technical Documentation** Not relevant

**Declared performance/s**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 14411:2012
Durability	pass for uses in interiors	EN 14411:2012
Durability	pass for uses in exteriors: resistance to freeze-thaw cycles	EN 14411:2012
Bond strength	≥ 0,5 N/mm <sup>2</sup> Cementitious adhesives, type C1	EN 14411:2012
Resistance to thermal shock	pass	EN 14411:2012
Cadmium release	NPD	EN 14411:2012
Lead release	NPD	EN 14411:2012

*NPD = no performance determined*

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

13.03.2023

Sto SE & Co. KGaA D-79780 Stühlingen

The current valid version of the declaration of performance is available at [www.sto.com/ce](http://www.sto.com/ce).



**Sto SE & Co. KGaA**  
Ehrenbachstraße 1  
D-79780 Stühlingen

**0101-0399-1**

**23**

**PROD5026 StoBrick 4000**  
**EN 14411:2012 ceramic tiles**

for cladding walls in interiors and exteriors

Reaction to fire	A1
Durability	pass for uses in interiors
Durability	pass for uses in exteriors: resistance to freeze-thaw cycles
Bond strength	≥ 0,5 N/mm <sup>2</sup> Cementitious adhesives, type C1
Resistance to thermal shock	pass
Cadmium release	NPD
Lead release	NPD