

Declaration of Performance for the construction product StoCleyer W

Unique identification code of the product-type	PROD4111 StoCleyer W
Intended use/s	factory-produced external render with organic binders for walls, ceilings, and piers in exterior areas as well as subsequent decorative design with incorporation of prefabricated render elements
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 3 (reaction to fire) System 4 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 15824:2017
Notified body/ies	0432
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2-s1, d0	EN 15824:2017
Water absorption	W 3	EN 15824:2017
Water vapour permeability	V 2	EN 15824:2017
Thermal conductivity	NPD	EN 15824:2017
Durability	NPD	EN 15824:2017
Dangerous substances	NPD	EN 15824:2017
Bond strength	NPD	EN 15824:2017

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

11.06.2026

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstr. 1
D-79780 Stühlingen

0101-0458-1

26

0432

PROD4111 StoCleyer W
EN 15824:2017 factory-produced external render with organic binders for walls, ceilings, and piers in exterior areas as well as subsequent decorative design with incorporation of prefabricated render elements

Reaction to fire	A2-s1, d0
Water absorption	W 3
Thermal conductivity	NPD
Bond strength	NPD
Durability	NPD
Water vapour permeability	V 2
Dangerous substances	NPD