

Declaration of Performance for the construction product StoColl CX

Unique identification code of the product-type	PROD3868 StoColl CX
Intended use/es	general purpose plastering mortar (GP) CS IV Onto walls, ceilings, pillars, and separating walls in exteriors and interiors
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 4 (reaction to fire) System 4 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 998-1:2016
Notified body/ies	MPA NRW NB 0432
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2-s1, d0	EN 998-1:2016
Water absorption	W_c2	EN 998-1:2016
Bond strength on concrete	$\geq 0,25 \text{ N/mm}^2$ / fracture pattern B	EN 998-1:2016
Durability	NPD	EN 998-1:2016
Dangerous substances	NPD	EN 998-1:2016
Water vapour diffusion-equivalent air layer thickness μ	≤ 25	EN 998-1:2016
Thermal conductivity	$\leq 0.61 \text{ W/(m}^{\circ}\text{K)}$ for P=50 %	EN 998-1:2016
Thermal conductivity	$\leq 0.66 \text{ W/(m}^{\circ}\text{K)}$ for P=90 %	EN 998-1:2016

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

09.04.2024

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstr. 1
D-79780 Stühlingen

0101-0306-2

18

NB 0432

PROD3868 StoColl CX
EN 998-1:2016 general purpose plastering mortar (GP) CS IV

Onto walls, ceilings, pillars, and separating walls in exteriors and interiors

Reaction to fire	A2-s1, d0
Water absorption	W _c 2
Water vapour diffusion-equivalent air layer thickness μ	≤ 25
Thermal conductivity	$\leq 0.61 \text{ W/(m}\cdot\text{K)}$ for P=50 % Table value
Thermal conductivity	$\leq 0.66 \text{ W/(m}\cdot\text{K)}$ for P=90 % Table value
Bond strength on concrete	$\geq 0,25 \text{ N/mm}^2$ / fracture pattern B
Durability	NPD
Dangerous substances	NPD