Declaration of Performance for the construction product
StoColl HT

CE

Unique identification code of the product-type	PROD4616 StoColl HT
Intended use/es	sealant for facades in interiors
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 3 (reaction to fire) System 3 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 15651-1:2012 type F-EXT-INT-CC: class 20HM
Notified body/ies	Ift Rosenheim GmbH NB 0757
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	E	EN 15651-1:2012
Durability	pass	EN 15651-1:2012
Resistance to flow	≤ 3 mm	EN 15651-1:2012
Volume loss	≤ 10 %	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	EN 15651-1:2012
Elongation at break	≥ 25 %	EN 15651-1:2012

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

29.10.2021
Sto SE & Co. KGaA D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.

CE

Sto SE & Co. KGaA

Ehrenbachstraße 1

D-79780 Stühlingen

| 01-0349-2 | 20 | NB 0757 |

PROD4616 StoColl HT
EN 15651-1:2012   type F-EXT-INT-CC: class 20HM   sealant for facades

in interiors

Reaction to fire	E
Durability	pass
Resistance to flow	≤ 3 mm
Volume loss	≤ 10 %
Release of chemicals dangerous to the environment and health	NPD
Elongation at break	≥ 25 %