

Declaration of Performance for the construction product

StoColl KM

Unique identification code of the product-type	PROD0616 StoColl KM
Intended use/es	normal hardening cementitious grout with reduced slip and extended open time, C1TE in exteriors and interiors
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 3 (reaction to fire) System 3 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 12004:2007 + A1:2012
Notified body/ies	MPA NRW NB 0432
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2-s1, d0	EN 12004:2007 + A1:2012
Release of dangerous substances	NPD	EN 12004:2007 + A1:2012
Bond strength	≥ 0,5 N/mm ² (Bond strength after dry storage)	EN 12004:2007 + A1:2012
Durability against effects of climate/warm storage	≥ 0.5 N/mm ² (bond strength after warm storage)	EN 12004:2007 + A1:2012
Durability against effects of climate/warm storage	≥ 0.5 N/mm ² (bond strength after storage in water)	EN 12004:2007 + A1:2012
Durability against effects of freeze-thaw cycle storage	≥ 0.5 N/mm ² (bond strength)	EN 12004:2007 + A1:2012

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

17.06.2023

Sto SE & Co. KGaA D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.