

Declaration of Performance for the construction product

StoCrete BE Bonding Agent

Unique identification code of the product-type	PROD0420 StoCrete BE Bonding Agent
Intended use/es	concrete repair product for structurally relevant repair Hand-applied mortar (3.1) Recasting with concrete or mortar (3.2) Increasing cover to reinforcement with additional mortar or concrete (7.1) Replacing contaminated or carbonated concrete (7.2)
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 2+ (for uses in buildings and civil engineering works) System 3 (for uses subject to reaction to fire regulations)
Harmonised standard	EN 1504-3
Notified body/ies	NB 0921 (system 2+) NB 0767 (system 3)
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	E	system 3 / EN 1504-3:2005
Dangerous substances	NPD	system 2+ / EN 1504-3
Chloride ion content	≤ 0.05 %	system 2+ / EN 1504-3
Slip resistance	NPD	system 2+ / EN 1504-3
Carbonation resistance	NPD	system 2+ / EN 1504-3
Restrained shrinking/swelling (dimensional stability)	1.82 MPa in conjunction with StoCrete BE Mörtel grob	system 2+ / EN 1504-3
Adhesive bond	2.08 MPa, in conjunction with StoCrete BE Mörtel grob	system 2+ / EN 1504-3
Capillary absorption	NPD	system 2+ / EN 1504-3
Thermal compatibility - Part 1: Freeze-thaw cycling	NPD in conjunction with StoCrete BE Mörtel grob	system 2+ / EN 1504-3
Thermal compatibility - Part 2: Thunder-shower cycling	2,24 MPa in conjunction with StoCrete BE Mörtel grob	system 2+ / EN 1504-3
Thermal compatibility - Part 4: Dry thermal cycling	2.58 MPa in conjunction with StoCrete BE Mörtel grob	system 2+ / EN 1504-3
Compressive strength	Class R 3	system 2+ / EN 1504-3
Modulus of elasticity	NPD	system 2+ / EN 1504-3

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

This copy was created by machine and is valid without signature.

10.06.2025

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstr. 1
D-79780 Stühlingen

0103-2000-2

09

NB 0921 (system 2+)
NB 0767 (system 3)

**PROD0420 StoCrete BE Bonding Agent
EN 1504-3**

concrete repair product for structurally relevant repair
Hand-applied mortar (3.1)
Recasting with concrete or mortar (3.2)
Increasing cover to reinforcement with additional mortar or concrete (7.1)
Replacing contaminated or carbonated concrete (7.2)

Reaction to fire	E
Dangerous substances	NPD
Chloride ion content	≤ 0.05 %
Slip resistance	NPD
Carbonation resistance	NPD
Restrained shrinking/swelling (dimensional stability)	1.82 MPa in conjunction with StoCrete BE Mörtel grob
Adhesive bond	2.08 MPa, in conjunction with StoCrete BE Mörtel grob
Capillary absorption	NPD
Thermal compatibility - Part 1: Freeze-thaw cycling	NPD in conjunction with StoCrete BE Mörtel grob
Thermal compatibility - Part 2: Thunder-shower cycling	2,24 MPa in conjunction with StoCrete BE Mörtel grob
Thermal compatibility - Part 4: Dry thermal cycling	2.58 MPa in conjunction with StoCrete BE Mörtel grob
Compressive strength	Class R 3
Modulus of elasticity	NPD