

Declaration of Performance for the construction product

StoCrete VM 630

Unique identification code of the product-type	PROD1171 StoCrete VM 630
Intended use/es	cementitious screed material for application in interiors
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 4 (for uses in interiors) System 4 (for uses in interiors subject to reaction to fire regulations)
Harmonised standard	EN 13813:2002
Notified body/ies	
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s for StoCrete VM 630 with StoCryl CP (primer):

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 in accordance with DECISION 96/603/EG, changed by DECISION 2000/605/EG and decision 2003/424/EG	system 4 / EN 13813:2002
Water vapour permeability	NPD	system 4 / EN 13813:2002
Flexural strength	F4	system 4 / EN 13813:2002
Sound absorption coefficient α_w	NPD	system 4 / EN 13813:2002
Water permeability	NPD	system 4 / EN 13813:2002
Abrasion resistance	NPD..The intended use of StoCrete VM 630 is always as a levelling mortar under cementitious screed material StoCrete VM 640. Avoid direct use.	system 4 / EN 13813:2002
Chemical resistance	NPD	system 4 / EN 13813:2002
Release of corrosive substances	CT	system 4 / EN 13813:2002
Impact sound insulation	NPD	system 4 / EN 13813:2002
Thermal resistance	NPD	system 4 / EN 13813:2002
Compressive strength	C20	system 4 / EN 13813:2002

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

09.11.2022

Sto SE & Co. KGaA D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstraße 1
D-79780 Stühlingen

0103-6066-1

10

PROD1171 StoCrete VM 630
EN 13813:2002

cementitious screed material for application in interiors

Reaction to fire	A1 in accordance with DECISION 96/603/EG, changed by DECISION 2000/605/EG and decision 2003/424/EG
Flexural strength	F4
Water vapour permeability	NPD
Sound absorption coefficient α_w	NPD
Water permeability	NPD
Abrasion resistance	NPD The intended use of StoCrete VM 630 is always as a levelling mortar under cementitious screed material StoCrete VM 640. Avoid direct use.
Chemical resistance	NPD
Release of corrosive substances	CT
Impact sound insulation	NPD
Thermal resistance	NPD
Compressive strength	C20