

Declaration of Performance for the construction product

StoCrete VM 640

Unique identification code of the product-type	PROD1172 StoCrete VM 640
Intended use/es	cementitious screed material for application in interiors
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 3 (for uses in interiors subject to reaction to fire regulations) System 4 (for uses in interiors)
Harmonised standard	EN 13813:2003
Notified body/ies	NB 0672 (system 3)
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s for StoCrete VM 640 with StoCryl CP (primer):

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{fi}	system 3 / EN 13813:2003
Water vapour permeability	NPD	system 4 / EN 13813:2003
Flexural strength	F7	system 4 / EN 13813:2003
Sound absorption coefficient α_w	NPD	system 4 / EN 13813:2003
Water permeability	NPD	system 4 / EN 13813:2003
Abrasion resistance	AR0.5..	system 4 / EN 13813:2003
Chemical resistance	NPD	system 4 / EN 13813:2003
Release of corrosive substances	CT	system 4 / EN 13813:2003
Impact sound insulation	NPD	system 4 / EN 13813:2003
Thermal resistance	NPD	system 4 / EN 13813:2003
Compressive strength	C40	system 4 / EN 13813:2003

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

09.11.2022

Sto SE & Co. KGaA D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstraße 1
D-79780 Stühlingen

0103-6067-1

10

NB 0672 (system 3)

PROD1172 StoCrete VM 640
EN 13813:2003

cementitious screed material for application in interiors

Reaction to fire	A1 _{fl}
Flexural strength	F7
Water vapour permeability	NPD
Sound absorption coefficient α_w	NPD
Water permeability	NPD
Abrasion resistance	AR0.5
Chemical resistance	NPD
Release of corrosive substances	CT
Impact sound insulation	NPD
Thermal resistance	NPD
Compressive strength	C40