

Declaration of Performance for the construction product StoDeco Frame - L

Unique identification code of the product-type	PROD3100 StoDeco Frame - L
Intended use/es	Three-dimensional facade elements made of volcanic lightweight granulate (Verolith) and epoxy resin for wall areas
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 3 (reaction to fire) System 4 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 15286:2013
Notified body/ies	MPA Stuttgart NB 0672
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2-s1, d0	EN 15286:2013
Water absorption	< 5%	EN 15286:2013
Thermal conductivity	T = 13 mm: 0.171 W/(m*K)	EN 15286:2013
Thermal conductivity	T = 26 mm: 0.170 W/(m*K)	EN 15286:2013
Release of dangerous substances	NPD	EN 15286:2013
Bending strength	≥ 2.5 N/mm ²	EN 15286:2013
Resistance to fixing	NPD	EN 15286:2013
Resistance to thermal shock	93,6 %	EN 15286:2013
Durability of flexural strength against freeze-thaw cycling	D = 20 mm: 98,7 %	EN 15286:2013
Adhesion strength of StoDeco Coll adhesive	1.099 kN/m ² (initial bond strength)	EN 15286:2013

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

14.03.2024

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstr. 1
D-79780 Stühlingen

0101-0407-1

23

NB 0672

PROD3100 StoDeco Frame - L

Three-dimensional facade elements made of volcanic lightweight granulate (Verolith) and epoxy resin for wall areas

Reaction to fire	A2-s1, d0
Water absorption	< 5%
Thermal conductivity	T = 13 mm: 0.171 W/(m*K)
Thermal conductivity	T = 26 mm: 0.170 W/(m*K)
Release of dangerous substances	NPD
Bending strength	≥ 2.5 N/mm ²
Resistance to fixing	NPD
Resistance to thermal shock	93,6 %
Durability of flexural strength against freeze-thaw cycling	D = 20 mm: 98,7 %
Adhesion strength of StoDeco Coll adhesive	1.099 kN/m ² (initial bond strength)