Declaration of performance for the building product
StoJet IHS 93

Identification code of the product type	PROD0160 StoJet IHS 93
Intended use	synthetic resin screed mortar
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System or systems of evaluation and verification of constancy of performance	system 4 (for applications in interiors) system 4 (for applications in interiors subject to regulations on reaction to fire)
Harmonised standard	EN 13813 SR-B2,0
Notified body	Not relevant
European Technical Assessment	Not relevant
Suitable technical documentation	Reaction to fire: E_{fl} (StoDok_20140624_1)

Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	E(fl) (StoDok_20140624_1)	EN 13813:2002
Tensile strength	≥B 2,0	EN 13813:2002
Sound absorption	NPD	EN 13813:2002
Water permeability	NPD	EN 13813:2002
Wear resistance	NPD..	EN 13813:2002
Chemical resistance	NPD	EN 13813:2002
Release of corrosive substances	SR	EN 13813:2002
Impact sound insulation	NPD	EN 13813:2002
Thermal resistance	NPD	EN 13813:2002
Impact resistance	NPD	EN 13813:2002

The performance of the product conforms with the declared performance. The manufacturer is solely responsible for compiling this declaration of performance.

Signed for the manufacturer and on behalf of the manufacturer of:

22.01.2015
Sto SE & Co. KGaA D-79780 Stühlingen

P.p. Dr. Hans Klein / Head of Approvals and Testing Procedures

Attachment: Safety data sheet

CE

Sto SE & Co. KGaA
Ehrenbachstraße 1
D-79780 Stühlingen

03-8004-1 **15**

PROD0160 StoJet IHS 93

EN 13813 SR-B2,0

synthetic resin screed mortar

Reaction to fire	E(fl) (StoDok_20140624_1)
Tensile strength	≥B 2,0
Sound absorption	NPD
Water permeability	NPD
Wear resistance	NPD
Chemical resistance	NPD
Release of corrosive substances	SR
Impact sound insulation	NPD
Thermal resistance	NPD
Impact resistance	NPD