

# Declaration of Performance for the construction product

## StoJet IHS 93

<b>Unique identification code of the product-type</b>	PROD0160 StoJet IHS 93
<b>Intended use/es</b>	Synthetic resin screed material
<b>Manufacturer</b>	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
<b>System/s of AVCP</b>	System 4 (for uses in interiors) System 4 (for uses in interiors subject to reaction to fire regulations)
<b>Harmonised standard</b>	EN 13813:2002
<b>Notified body/ies</b>	
<b>European Assessment Document</b>	Not relevant
<b>European Technical Assessment</b>	Not relevant
<b>Technical Assessment Body</b>	Not relevant
<b>Appropriate Technical Documentation and/or Specific Technical Documentation</b>	reaction to fire: E <sub>fl</sub> (StoDok_20140624_1)

### Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	E <sub>fl</sub> (StoDok_20140624_1)	system 4 / EN 13813:2002
Bond strength	≥B 2,0	system 4 / EN 13813:2002
Sound absorption coefficient α <sub>w</sub>	NPD	system 4 / EN 13813:2002
Water permeability	NPD	system 4 / EN 13813:2002
Abrasion resistance	NPD..	system 4 / EN 13813:2002
Chemical resistance	NPD	system 4 / EN 13813:2002
Release of corrosive substances	SR	system 4 / EN 13813:2002
Impact sound insulation	NPD	system 4 / EN 13813:2002
Thermal resistance	NPD	system 4 / EN 13813:2002
Impact resistance	NPD	system 4 / EN 13813:2002

*NPD = no performance determined*

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

12.03.2026

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at [www.sto.com/ce](http://www.sto.com/ce).



Sto SE & Co. KGaA  
Ehrenbachstr. 1  
D-79780 Stühlingen

**0103-8004-2**

**15**

**PROD0160 StoJet IHS 93  
EN 13813:2002**

Synthetic resin screed material

Reaction to fire	E <sub>fi</sub> (StoDok_20140624_1)
Bond strength	≥B 2,0
Sound absorption coefficient α <sub>w</sub>	NPD
Water permeability	NPD
Abrasion resistance	NPD
Chemical resistance	NPD
Release of corrosive substances	SR
Impact sound insulation	NPD
Thermal resistance	NPD
Impact resistance	NPD