

Declaration of Performance for the construction product

StoJet PIH 200

Unique identification code of the product-type	PROD2341 StoJet PIH 200
Intended use/es	concrete injection products concrete injection for ductile filling of cracks, voids, and interstices U(D1) W(1)(1/2/3/4) (8/30)
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 2+ (for uses in buildings and civil engineering works)
Harmonised standard	EN 1504-5:2006
Notified body/ies	NB 0921 (system 2+)
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s		
Essential characteristics	Performance	Harmonised technical specification
Durability	pass	EN 1504-5:2006
Glass transition temperature	-31 °C	EN 1504-5:2006
Corrosion behaviour	deemed to have no corrosive effect	EN 1504-5:2006
Watertightness	D 1	EN 1504-5:2006
Elongation capacity	> 10 %	EN 1504-5:2006
Dangerous substances	NPD	EN 1504-5:2006
Bond strength	> 0.05 MPa	EN 1504-5:2006
Workability: effect on polymeric inserts	successfully tested	EN 1504-5:2006
Workability: injectability into dry medium	8 °C / 0.2 21 °C / 0.1 30 °C / 0.1 * Temperature/injectability class	EN 1504-5:2006
Workability: injectability into non-dry medium	8 °C / 1.2 / 0.2 21 °C / 1.2 / 0.1 30 °C / 1.2 / 0.1 * Temperature/moisture state of the crack/injectability class	EN 1504-5:2006

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

12.12.2022

Sto SE & Co. KGaA D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstraße 1
D-79780 Stühlingen

0103-8002-1

15

NB 0921 (system 2+)

PROD2341 StoJet PIH 200
EN 1504-5:2006

concrete injection products
concrete injection for ductile filling of cracks, voids, and interstices
U(D1) W(1)(1/2/3/4) (8/30)

Durability	pass
Glass transition temperature	-31 °C
Corrosion behaviour	deemed to have no corrosive effect
Watertightness	D 1
Elongation capacity	> 10 %
Dangerous substances	NPD
Bond strength	> 0.05 MPa
Workability: effect on polymeric inserts	successfully tested
Workability: injectability into dry medium	8 °C / 0.2 21 °C / 0.1 30 °C / 0.1 * Temperature/injectability class
Workability: injectability into non-dry medium	8 °C / 1.2 / 0.2 21 °C / 1.2 / 0.1 30 °C / 1.2 / 0.1 * Temperature/moisture state of the crack/injectability class