

Declaration of Performance for the construction product StoLevell Calce FS

Unique identification code of the product-type	PROD2122 StoLevell Calce FS
Intended use/s	lightweight plastering mortar (LW) CS II onto walls, ceilings, pillars, and separating walls in interiors
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 4 (reaction to fire) System 4 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 998-1:2016
Notified body/ies	MPA NRW NB 0432
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2-s1, d0	EN 998-1:2016
Water absorption	W_c 0	EN 998-1:2016
Bond strength on concrete	$\geq 0,25$ N/mm ² / fracture pattern B	EN 998-1:2016
Durability	NPD	EN 998-1:2016
Dangerous substances	NPD	EN 998-1:2016
Water vapour diffusion-equivalent air layer thickness μ	≤ 20	EN 998-1:2016
Thermal conductivity	$\leq 0,33$ W/(m*K) für P=50%	EN 998-1:2016
Thermal conductivity	$\leq 0,36$ W/(m*K) für P=90%	EN 998-1:2016

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

09.04.2024

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstr. 1
D-79780 Stühlingen

01-0210-4

14

NB 0432

PROD2122 StoLevell Calce FS
EN 998-1:2016 lightweight plastering mortar (LW) CS II
onto walls, ceilings, pillars, and separating walls in interiors

Reaction to fire	A2-s1, d0
Water absorption	W_c 0
Water vapour diffusion-equivalent air layer thickness μ	≤ 20
Thermal conductivity	$\leq 0,33 \text{ W/(m}\cdot\text{K)}$ für P=50% Table value
Thermal conductivity	$\leq 0,36 \text{ W/(m}\cdot\text{K)}$ für P=90% Table value
Bond strength on concrete	$\geq 0,25 \text{ N/mm}^2$ / fracture pattern B
Durability	NPD
Dangerous substances	NPD