

Declaration of Performance for the construction product StoLevell Duo plus QS

| | |
|--|---|
| Unique identification code of the product-type | PROD0112 StoLevell Duo plus QS |
| Intended use/es | general purpose plastering mortar (GP) CS III Onto walls, ceilings, pillars, and separating walls in exteriors and interiors |
| Manufacturer | Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen |
| System/s of AVCP | System 4 (reaction to fire) System 4 (applies to all other "Essential characteristics" in the table) |
| Harmonised standard | EN 998-1:2016 |
| Notified body/ies | Not relevant |
| European Assessment Document | Not relevant |
| European Technical Assessment | Not relevant |
| Technical Assessment Body | Not relevant |
| Appropriate Technical Documentation and/or Specific Technical Documentation | Not relevant |

Declared performance/s

| Essential characteristics | Performance | Harmonised technical specification |
|---|--|------------------------------------|
| Reaction to fire | A2-s1, d0 | EN 998-1:2016 |
| Water absorption | W_c 1 | EN 998-1:2016 |
| Bond strength on concrete | $\geq 0,25$ N/mm ² / fracture pattern B | EN 998-1:2016 |
| Durability | NPD | EN 998-1:2016 |
| Dangerous substances | NPD | EN 998-1:2016 |
| Water vapour diffusion-equivalent air layer thickness μ | ≤ 25 | EN 998-1:2016 |
| Thermal conductivity | $\leq 0,45$ W/(m*K) für P=50% | EN 998-1:2016 |
| Thermal conductivity | $\leq 0,49$ W/(m*K) für P=90% | EN 998-1:2016 |

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

05.10.2023

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstr. 1
D-79780 Stühlingen

0101-0088-3

07

PROD0112 StoLevel Duo plus QS
EN 998-1:2016 general purpose plastering mortar (GP) CS III

Onto walls, ceilings, pillars, and separating walls in exteriors and interiors

| | |
|---|---|
| Reaction to fire | A2-s1, d0 |
| Water absorption | W _c 1 |
| Water vapour diffusion-equivalent air layer thickness μ | ≤ 25 |
| Thermal conductivity | $\leq 0,45 \text{ W}/(\text{m}\cdot\text{K})$ für P=50% Table value |
| Thermal conductivity | $\leq 0,49 \text{ W}/(\text{m}\cdot\text{K})$ für P=90% Table value |
| Bond strength on concrete | $\geq 0,25 \text{ N}/\text{mm}^2$ / fracture pattern B |
| Durability | NPD |
| Dangerous substances | NPD |