



Declaration of Performance for the construction product

StoLevell In AS

Unique identification code of the product-type	PROD0232 StoLevell In AS render/plaster with organic binding agents <i>See the container imprint for the batch number.</i>
Intended use/es	onto walls, ceilings, pillars, and separating walls in interiors
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 3 (reaction to fire) system 4 (applies to all other "Essential characteristics" in the table)

Harmonised standard	EN 15824:2017
Notified body/ies	MPA Stuttgart NB 0672

European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	AVCP system	Harmonised technical specification
Reaction to fire	A2-s1, d0	System 3	EN 15824:2017
Water absorption	NPD		EN 15824:2017
Water vapour permeability	V 1		EN 15824:2017
Thermal conductivity	NPD		EN 15824:2017
Durability	NPD		EN 15824:2017
Dangerous substances	NPD		EN 15824:2017
Bond strength	1,5 MPa		EN 15824:2017

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



18.04.2019
Sto SE & Co. KGaA D-79780 Stühlingen

Francisco Ramos / Head of Business Fields Facade and Interiors

Attachment: Safety Data Sheet

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA

Ehrenbachstraße 1

D-79780 Stühlingen

01-0027-3

10

NB 0672

PROD0232 StoLevell In AS

EN 15824:2017 render/plaster with organic binding agents

onto walls, ceilings, pillars, and separating walls in interiors

Reaction to fire	A2-s1, d0
Water absorption	NPD
Thermal conductivity	NPD
Bond strength	1,5 MPa
Durability	NPD
Water vapour permeability	V 1
Dangerous substances	NPD