

Declaration of Performance for the construction product StoLevell In FF

Unique identification code of the product-type	PROD5417 StoLevell In FF
Intended use/es	filler for gypsum plasterboards type 3A joint filling compound
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 3 (reaction to fire) System 3 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 13963:2005
Notified body/ies	Tecnalía NB 1292
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2-s1, d0	EN 13963:2005
Flexural strength	> 300 (N)	EN 13963:2005

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

26.06.2025

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstr. 1
D-79780 Stühlingen

0101-0446-2

25

NB 1292

PROD5417 StoLevel In FF
filler for gypsum plasterboards type 3A
joint filling compound

Reaction to fire	A2-s1, d0
Flexural strength	> 300 (N)