

Declaration of Performance for the construction product



StoLevell In Mineral

Unique identification code of the product-type	PROD0732 StoLevell In Mineral general purpose plastering mortar (GP) CS III <i>See the container imprint for the batch number.</i>
Intended use/es	onto walls, ceilings, pillars, and separating walls in interiors
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 4 (reaction to fire) System 4 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 998-1:2016
Notified body/ies	Not relevant
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	AVCP system	Harmonised technical specification
Reaction to fire	A2-s1, d0	System 4	EN 998-1:2016
Water absorption	W_c 0		EN 998-1:2016
Bond strength on concrete	$\geq 0,25$ N/mm ² / fracture pattern B		EN 998-1:2016
Durability	NPD		EN 998-1:2016
Dangerous substances	NPD		EN 998-1:2016
Water vapour diffusion-equivalent air layer thickness μ	≤ 25		EN 998-1:2016
Thermal conductivity	≤ 0.61 W/(m*K) for P=50 %		EN 998-1:2016
Thermal conductivity	≤ 0.66 W/(m*K) for P=90 %		EN 998-1:2016

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



16.09.2020
Sto SE & Co. KGaA D-79780 Stühlingen

Francisco Ramos / Head of Business Fields Facade and Interiors

Attachment: Safety Data Sheet

The current valid version of the declaration of performance is available at www.sto.com/ce.

CE	<p>Sto SE & Co. KGaA Ehrenbachstraße 1 D-79780 Stühlingen</p>
01-0091-3	09
<p>PROD0732 StoLevel In Mineral EN 998-1:2016 general purpose plastering mortar (GP) CS III CS III onto walls, ceilings, pillars, and separating walls in interiors</p>	
Reaction to fire	A2-s1, d0
Water absorption	W _c 0
Water vapour diffusion-equivalent air layer thickness μ	≤ 25
Thermal conductivity	≤ 0.61 W/(m*K) for P=50 %Table value ≤ 0.66 W/(m*K) for P=90 %Table value
Bond strength on concrete	≥ 0,25 N/mm ² / fracture pattern B
Durability	NPD
Dangerous substances	NPD