



Declaration of Performance for the construction product

StoLevell Uni

Unique identification code of the product-type	PROD0907 StoLevell Uni general purpose plastering mortar (GP) CS IV <i>See the container imprint for the batch number.</i>
Intended use/es	Onto walls, ceilings, pillars, and separating walls in exteriors and interiors
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	system 4 (reaction to fire) system 4 (applies to all other "Essential characteristics" in the table)

Harmonised standard	EN 998-1:2016
Notified body/ies	Not relevant

European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	AVCP system	Harmonised technical specification
Reaction to fire	A2-s1, d0	system 4	EN 998-1:2016
Water absorption	W _c 2		EN 998-1:2016
Bond strength on concrete	≥ 0,25 N/mm ² / fracture pattern B		EN 998-1:2016
Durability	NPD		EN 998-1:2016
Dangerous substances	NPD		EN 998-1:2016
Water vapour diffusion-equivalent air layer thickness μ	≤ 25		EN 998-1:2016
Thermal conductivity	≤ 0,45 W/(m*K) für P=50%		EN 998-1:2016
Thermal conductivity	≤ 0,49 W/(m*K) für P=90%		EN 998-1:2016

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



04.02.2019
Sto SE & Co. KGaA D-79780 Stühlingen

Dr Eike Messow/Head of Shared Services

Attachment: Safety Data Sheet

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA

Ehrenbachstraße 1

D-79780 Stühlingen

01-0094-4

07

PROD0907 StoLevel Uni

EN 998-1:2016 general purpose plastering mortar (GP) CS IV

Onto walls, ceilings, pillars, and separating walls in exteriors and interiors

Reaction to fire	A2-s1, d0
Water absorption	W _c 2
Water vapour diffusion-equivalent air layer thickness μ	≤ 25
Thermal conductivity	$\leq 0,45 \text{ W/(m}\cdot\text{K)}$ für P=50%Table value
	$\leq 0,49 \text{ W/(m}\cdot\text{K)}$ für P=90%Table value
Bond strength on concrete	$\geq 0,25 \text{ N/mm}^2$ / fracture pattern B
Durability	NPD
Dangerous substances	NPD