

Declaration of Performance for the construction product

StoMiral[®] K



Unique identification code of the product-type	PROD0761 StoMiral [®] K
Intended use/es	coloured plastering mortar (CR) CS II Onto walls, ceilings, pillars, and separating walls in exteriors and interiors
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 4 (reaction to fire) System 4 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 998-1:2016
Notified body/ies	Not relevant
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 998-1:2016
Water absorption	W _c 2	EN 998-1:2016
Bond strength on concrete	≥ 0,08 N/mm ² / fracture pattern B	EN 998-1:2016
Durability	NPD	EN 998-1:2016
Dangerous substances	NPD	EN 998-1:2016
Water vapour diffusion-equivalent air layer thickness μ	≤ 20	EN 998-1:2016
Thermal conductivity	≤ 0,45 W/(m*K) für P=50%	EN 998-1:2016
Thermal conductivity	≤ 0,49 W/(m*K) für P=90%	EN 998-1:2016

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

11.03.2021
Sto SE & Co. KGaA D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstraße 1
D-79780 Stühlingen

01-0099-5

05

PROD0761 StoMiral® K
EN 998-1:2016 coloured plastering mortar (CR) CS II

Onto walls, ceilings, pillars, and separating walls in exteriors and interiors

Reaction to fire	A1
Water absorption	W_c 2
Water vapour diffusion-equivalent air layer thickness μ	≤ 20
Thermal conductivity	$\leq 0,45$ W/(m*K) für P=50%Table value $\leq 0,49$ W/(m*K) für P=90%Table value
Bond strength on concrete	$\geq 0,08$ N/mm ² / fracture pattern B
Durability	NPD
Dangerous substances	NPD