

Declaration of Performance for the construction product StoMiral Scratch Render

Unique identification code of the product-type	PROD4983 StoMiral Scratch Render
Intended use/es	coloured plastering mortar (CR) CS I onto walls, ceilings and pillars in exteriors
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 4 (reaction to fire) System 4 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 998-1:2016
Notified body/ies	Not relevant
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	CWFT (reaction to fire)

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 998-1:2016
Water absorption	W_c 2	EN 998-1:2016
Bond strength on concrete	$\geq 0,08$ N/mm ² / fracture pattern A, B, C	EN 998-1:2016
Durability	NPD	EN 998-1:2016
Dangerous substances	NPD	EN 998-1:2016
Water vapour diffusion-equivalent air layer thickness μ	≤ 20	EN 998-1:2016
Thermal conductivity	≤ 0.82 W/(m*K) for P=50 %	EN 998-1:2016
Thermal conductivity	≤ 0.89 W/(m*K) for P=90 %	EN 998-1:2016

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

20.03.2024

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstr. 1
D-79780 Stühlingen

0101-0095-2

17

**PROD4983 StoMiral Scratch Render
EN 998-1:2016 coloured plastering mortar (CR) CS I**

onto walls, ceilings and pillars in exteriors

Reaction to fire	A1
Water absorption	W _c 2
Water vapour diffusion-equivalent air layer thickness μ	≤ 20
Thermal conductivity	$\leq 0.82 \text{ W}/(\text{m}\cdot\text{K})$ for P=50 % Table value
Thermal conductivity	$\leq 0.89 \text{ W}/(\text{m}\cdot\text{K})$ for P=90 % Table value
Bond strength on concrete	$\geq 0,08 \text{ N}/\text{mm}^2$ / fracture pattern A, B, C
Durability	NPD
Dangerous substances	NPD