Declaration of performance for the building product
StoMurisol BD 2K

Identification code of the product type	PROD0082 StoMurisol BD 2K
Intended use	for waterproofing building elements in contact with the ground
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System or systems of evaluation and verification of constancy of performance	System 3
Harmonised standard	EN 15814 plastic-modified bitumen coating (PMB)
Notified body	test institute Hoch NB 1508 MPA NRW NB 0432 carried out the initial test of the building product with regard to reaction to fire in accordance with system 3 and issued a test / classification report.
European Technical Assessment	Not relevant
Suitable technical documentation	Not relevant

Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	E	EN 15814:2013-01
Watertightness	W2A	EN 15814:2013-01
Crack bridging capability	CB2	EN 15814:2013-01
Resistance to water	no discolouration of the water no stripping from the inlay	EN 15814:2013-01
Flexibility at low temperatures	no cracks	EN 15814:2013-01
Dimensional stability at high temperatures	no slipping and draining	EN 15814:2013-01
Durability of watertightness and reaction to fire	meets	EN 15814:2013-01
Compressive strength	C2A	EN 15814:2013-01

The performance of the product conforms with the declared performance. The manufacturer is solely responsible for compiling this declaration of performance.

Signed for the manufacturer and on behalf of the manufacturer of:

26.08.2014
Sto SE & Co. KGaA D-79780 Stühlingen

P.p. Dr. Hans Klein / Head of Approvals and Testing Procedures

Attachment: Safety data sheet

Sto SE & Co. KGaA
Ehrenbachstraße 1
D-79780 Stühlingen

01-0209-1 **13** **1508, 0432**

PROD0082 StoMurisol BD 2K
EN 15814 plastic-modified bitumen coating (PMB)

for waterproofing building elements in contact with the ground

Reaction to fire	E
Watertightness	W2A
Crack bridging capability	CB2
Resistance to water	no discolouration of the water no stripping from the inlay
Flexibility at low temperatures	no cracks
Dimensional stability at high temperatures	no slipping and draining
Durability of watertightness and reaction to fire	meets
Compressive strength	C2A