

Declaration of Performance for the construction product

StoMurisol SP fine

Unique identification code of the product-type	PROD0407 StoMurisol SP fine
Intended use/es	renovation render (R) Onto walls, ceilings, pillars, and separating walls in exteriors and interiors
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 4 (reaction to fire) System 4 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 998-1:2016
Notified body/ies	-
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 998-1:2016
Water absorption	$\geq 0.3 \text{ kg/m}^2$ after 24 h	EN 998-1:2016
Bond strength on concrete	$\geq 0,08 \text{ N/mm}^2$ / fracture pattern A, B, C	EN 998-1:2010
Durability	NPD	EN 998-1:2016
Dangerous substances	NPD	EN 998-1:2016
Water vapour diffusion-equivalent air layer thickness μ	≤ 15	EN 998-1:2016
Thermal conductivity	$\leq 0.82 \text{ W/(m}^*\text{K)}$ for P=50 %	EN 998-1:2016
Thermal conductivity	$\leq 0.89 \text{ W/(m}^*\text{K)}$ for P=90 %	EN 998-1:2016
Water penetration following water absorption test	$\leq 5 \text{ mm}$	EN 998-1:2016

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

18.11.2025

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstr. 1
D-79780 Stühlingen

0101-0110-4

05 -

**PROD0407 StoMurisol SP fine
EN 998-1:2016 renovation render (R)**

Onto walls, ceilings, pillars, and separating walls in exteriors and interiors

Reaction to fire	A1
Water absorption	≥ 0.3 kg/m ² after 24 h
Water vapour diffusion-equivalent air layer thickness μ	≤ 15
Thermal conductivity	≤ 0.82 W/(m*K) for P=50 % Table value
Thermal conductivity	≤ 0.89 W/(m*K) for P=90 % Table value
Bond strength on concrete	≥ 0,08 N/mm ² / fracture pattern A, B, C
Durability	NPD
Dangerous substances	NPD
Water penetration following water absorption test	≤ 5 mm