

Declaration of Performance for the construction product

StoPma CS 100

Unique identification code of the product-type	PROD4605 StoPma CS 100
Intended use/es	Synthetic resin screed material
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 4 (for uses in interiors) System 4 (for uses in interiors subject to reaction to fire regulations)
Harmonised standard	EN 13813:2002
Notified body/ies	
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	reaction to fire: E _{fi} (StoDok_20140624_2)

Declared performance/s	EN 13813:	
Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	E _{fi} (StoDok_20140624_2)	system 4 / EN 13813:2002
Bond strength	≥ B 1.5	system 4 / EN 13813:2002
Sound absorption coefficient α _w	NPD	system 4 / EN 13813:2002
Water permeability	NPD	system 4 / EN 13813:2002
Abrasion resistance	≤ AR1..	system 4 / EN 13813:2002
Chemical resistance	NPD	system 4 / EN 13813:2002
Release of corrosive substances	SR	system 4 / EN 13813:2002
Impact sound insulation	NPD	system 4 / EN 13813:2002
Thermal resistance	NPD	system 4 / EN 13813:2002
Impact resistance	≥IR4	system 4 / EN 13813:2002

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

12.12.2022

Sto SE & Co. KGaA D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.

		Sto SE & Co. KGaA Ehrenbachstraße 1 D-79780 Stühlingen	
		0103-6127-2	22
PROD4605 StoPma CS 100 EN 13813: 2002 Synthetic resin screed material			
Reaction to fire	E _{fl} (StoDok_20140624_2)		
Bond strength	≥ B 1.5		
Sound absorption coefficient α_w	NPD		
Water permeability	NPD		
Abrasion resistance	≤ AR1		
Chemical resistance	NPD		
Release of corrosive substances	SR		
Impact sound insulation	NPD		
Thermal resistance	NPD		
Impact resistance	≥ IR4		