

# Declaration of Performance for the construction product StoPox WL 110

<b>Unique identification code of the product-type</b>	PROD0687 StoPox WL 110
<b>Intended use/es</b>	Synthetic resin screed material
<b>Manufacturer</b>	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
<b>System/s of AVCP</b>	System 4 (for uses in interiors) System 4 (for uses in interiors subject to reaction to fire regulations)
<b>Harmonised standard</b>	EN 13813:2002
<b>Notified body/ies</b>	
<b>European Technical Assessment</b>	Not relevant
<b>Technical Assessment Body</b>	Not relevant
<b>Appropriate Technical Documentation and/or Specific Technical Documentation</b>	reaction to fire: E <sub>fl</sub> (StoDok_20140624_2)

## Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	E <sub>fl</sub> (StoDok_20140624_2)	system 4 / EN 13813:2002
Bond strength	≥ B 1.5	system 4 / EN 13813:2002
Sound absorption coefficient α <sub>w</sub>	NPD	system 4 / EN 13813:2002
Water permeability	NPD	system 4 / EN 13813:2002
Abrasion resistance	≤ AR1..	system 4 / EN 13813:2002
Chemical resistance	NPD	system 4 / EN 13813:2002
Release of corrosive substances	SR	system 4 / EN 13813:2002
Impact sound insulation	NPD	system 4 / EN 13813:2002
Thermal resistance	NPD	system 4 / EN 13813:2002
Impact resistance	≥IR4	system 4 / EN 13813:2002

*NPD = no performance determined*

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Signature Francisco Ramos

This copy was created by machine and is valid without signature.

10.07.2025

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at [www.sto.com/ce](http://www.sto.com/ce).



Sto SE & Co. KGaA  
Ehrenbachstr. 1  
D-79780 Stühlingen

0103-6091-1

25

**PROD0687 StoPox WL 110  
EN 13813:2002**

Synthetic resin screed material

Reaction to fire	E <sub>fl</sub> (StoDok_20140624_2)
Bond strength	≥ B 1.5
Sound absorption coefficient α <sub>w</sub>	NPD
Water permeability	NPD
Abrasion resistance	≤ AR1
Chemical resistance	NPD
Release of corrosive substances	SR
Impact sound insulation	NPD
Thermal resistance	NPD
Impact resistance	≥ IR4