

# Declaration of Performance for the construction product



## StoPrefa Level 200

<b>Unique identification code of the product-type</b>	PROD0332 StoPrefa Level 200 render/plaster with organic binding agents <i>See the container imprint for the batch number.</i>
<b>Intended use/es</b>	Onto walls, ceilings, pillars, and separating walls in exteriors and interiors
<b>Manufacturer</b>	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
<b>System/s of AVCP</b>	System 3 (reaction to fire) system 4 (applies to all other "Essential characteristics" in the table)

<b>Harmonised standard</b>	EN 15824:2017
<b>Notified body/ies</b>	MPA Stuttgart NB 0672

<b>European Assessment Document</b>	Not relevant
<b>European Technical Assessment</b>	Not relevant
<b>Technical Assessment Body</b>	Not relevant
<b>Appropriate Technical Documentation and/or Specific Technical Documentation</b>	Not relevant

### Declared performance/s

Essential characteristics	Performance	AVCP system	Harmonised technical specification
Reaction to fire	A2-s1, d0	System 3	EN 15824:2017
Water absorption	NPD		EN 15824:2017
Water vapour permeability	V 2		EN 15824:2017
Thermal conductivity	NPD		EN 15824:2017
Durability	NPD		EN 15824:2017
Dangerous substances	NPD		EN 15824:2017
Bond strength	≥ 0,3 MPa		EN 15824:2017

*NPD = no performance determined*

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



25.04.2019  
Sto SE & Co. KGaA D-79780 Stühlingen

Francisco Ramos / Head of Business Fields Facade and Interiors

Attachment: Safety Data Sheet

The current valid version of the declaration of performance is available at [www.sto.com/ce](http://www.sto.com/ce).



Sto SE & Co. KGaA

Ehrenbachstraße 1

D-79780 Stühlingen

01-0051-3

10

NB 0672

**PROD0332 StoPrefa Levell 200**

**EN 15824:2017 render/plaster with organic binding agents**

Onto walls, ceilings, pillars, and separating walls in exteriors and interiors

Reaction to fire	A2-s1, d0
Water absorption	NPD
Thermal conductivity	NPD
Bond strength	≥ 0,3 MPa
Durability	NPD
Water vapour permeability	V 2
Dangerous substances	NPD