

Declaration of Performance for the construction product

StoPur SL 125

| | |
|--|--|
| Unique identification code of the product-type | PROD4533 StoPur SL 125 |
| Intended use/es | Synthetic resin screed material |
| Manufacturer | Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen |
| System/s of AVCP | System 4 (for uses in interiors) System 4 (for uses in interiors subject to reaction to fire regulations) |
| Harmonised standard | EN 13813:2002 |
| Notified body/ies | |
| European Assessment Document | Not relevant |
| European Technical Assessment | Not relevant |
| Technical Assessment Body | Not relevant |
| Appropriate Technical Documentation and/or Specific Technical Documentation | reaction to fire: E _{fi} (StoDok_20140624_2) |
| Declared performance/s | The product is used in the coating system: StoFloor Comfort Elastic CL 125 consisting of the components: StoPox GH 500 StoPur CL 125 StoPur AL 125 StoPur SL 125 StoPur WV 152 StoPur WV 202 |

| Essential characteristics | Performance | Harmonised technical specification |
|---|-------------------------------------|------------------------------------|
| Reaction to fire | E _{fi} (StoDok_20140624_2) | system 4 / EN 13813:2002 |
| Bond strength | ≥ B 1.5 | system 4 / EN 13813:2002 |
| Sound absorption coefficient α_w | NPD | system 4 / EN 13813:2002 |
| Water permeability | NPD | system 4 / EN 13813:2002 |
| Abrasion resistance | ≤ AR1.. | system 4 / EN 13813:2002 |
| Chemical resistance | NPD | system 4 / EN 13813:2002 |
| Release of corrosive substances | SR | system 4 / EN 13813:2002 |
| Impact sound insulation | NPD | system 4 / EN 13813:2002 |
| Thermal resistance | NPD | system 4 / EN 13813:2002 |
| Impact resistance | ≥ IR4 | system 4 / EN 13813:2002 |

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

14.12.2022

Sto SE & Co. KGaA D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.

| | | | |
|--|--|---------------------------|------------------|
|  | <p>Sto SE & Co. KGaA Ehrenbachstraße 1 D-79780 Stühlingen</p> | <p>0103-6118-2</p> | <p>22</p> |
| <p>PROD4533 StoPur SL 125 EN 13813: 2002 Synthetic resin screed material</p> | | | |
| Reaction to fire | E _{fl} (StoDok_20140624_2) | | |
| Bond strength | ≥ B 1.5 | | |
| Sound absorption coefficient α_w | NPD | | |
| Water permeability | NPD | | |
| Abrasion resistance | ≤ AR1 | | |
| Chemical resistance | NPD | | |
| Release of corrosive substances | SR | | |
| Impact sound insulation | NPD | | |
| Thermal resistance | NPD | | |
| Impact resistance | ≥ IR4 | | |