

Declaration of Performance for the construction product StoSeal Band AD-250

Unique identification code of the product-type	PROD5437 StoSeal Band AD-250
Intended use/es	vapour control layers (type A); construction sealing foil (0.6 mm thick)
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 3 (reaction to fire) System 3 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 13984:2013
Notified body/ies	0370
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	E	EN 13984:2013
Water vapour permeability	≤ 50.000	EN 13984:2013
Watertightness	resistant at 2 kPa	EN 13984:2013
Tensile strength	≥ 6 MPa	EN 13984:2013
Elongation	≥ 250%	EN 13984:2013
Resistance to impact load	NPD	EN 13984:2013
Shear adhesion of joint seams	NPD	EN 13984:2013
Ageing resistance	pass	EN 13984:2013
Resistance to tearing	≥ 10 N	EN 13984:2013

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

05.02.2026

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstr. 1
D-79780 Stühlingen

0101-0448-1

25

0370

PROD5437 StoSeal Band AD-250
EN 13984:2013 vapour control layers (type A); construction sealing foil (0.6 mm thick)

Reaction to fire	E
Water vapour permeability	≤ 50.000
Watertightness	resistant at 2 kPa
Tensile strength	≥ 6 MPa
Elongation	≥ 250%
Resistance to impact load	NPD
Shear adhesion of joint seams	NPD
Ageing resistance	pass
Resistance to tearing	≥ 10 N