

# Declaration of Performance for the construction product

## StoSil<sup>®</sup> MP

<b>Unique identification code of the product-type</b>	PROD0673 StoSil <sup>®</sup> MP
<b>Intended use/es</b>	render/plaster with organic binding agents onto walls, ceilings and pillars in exteriors
<b>Manufacturer</b>	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
<b>System/s of AVCP</b>	System 3 (reaction to fire) System 4 (applies to all other "Essential characteristics" in the table)
<b>Harmonised standard</b>	EN 15824:2017
<b>Notified body/ies</b>	MPA NRW NB 0432
<b>European Assessment Document</b>	Not relevant
<b>European Technical Assessment</b>	Not relevant
<b>Technical Assessment Body</b>	Not relevant
<b>Appropriate Technical Documentation and/or Specific Technical Documentation</b>	Not relevant

### Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2-s1, d0	EN 15824:2017
Water absorption	W 3	EN 15824:2017
Water vapour permeability	V 1	EN 15824:2017
Thermal conductivity	NPD	EN 15824:2017
Durability	NPD	EN 15824:2017
Dangerous substances	NPD	EN 15824:2017
Bond strength	≥ 0,3 MPa	EN 15824:2017

*NPD = no performance determined*

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

11.06.2024

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at [www.sto.com/ce](http://www.sto.com/ce).



Sto SE & Co. KGaA  
Ehrenbachstr. 1  
D-79780 Stühlingen

0101-0059-6

10

NB 0432

**PROD0673 StoSil® MP**  
**EN 15824:2017 render/plaster with organic binding agents**

onto walls, ceilings and pillars in exteriors

Reaction to fire	A2-s1, d0
Water absorption	W 3
Thermal conductivity	NPD
Bond strength	≥ 0,3 MPa
Durability	NPD
Water vapour permeability	V 1
Dangerous substances	NPD