

Declaration of Performance for the construction product StoSilent Board 205 C

Unique identification code of the product-type	PROD4595 StoSilent Board 205 C
Intended use/es	Ceiling membrane of suspended ceiling Inside of buildings
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 3 (reaction to fire) System 3 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 13964:2014
Notified body/ies	0672
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2-s1, d0 StoSilent Distance C system	EN 13964:2014
Sound absorption coefficient α_w	See test report M 100 960/28 of 4 August 2021 Müller BBM	EN 13964:2014
Release of dangerous substances	no release of asbestos and formaldehyde	EN 13964:2014

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

18.11.2025

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstr. 1
D-79780 Stühlingen

0101-0370-2

21

0672

PROD4595 StoSilent Board 205 C
Ceiling membrane of suspended ceiling

Inside of buildings

Reaction to fire

A2-s1, d0 StoSilent Distance C system

Sound absorption coefficient α_w

See test report M 100 960/28 of 4 August 2021 Müller BBM

Release of dangerous substances

no release of asbestos and formaldehyde