

Declaration of Performance for the construction product



StoSilent Coll MW-G

Unique identification code of the product-type PROD4204 StoSilent Coll MW-G
gypsum-based adhesive
See the container imprint for the batch number.

Intended use/es onto walls, ceilings, pillars, and separating walls in interiors

Manufacturer Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

System/s of AVCP CWFT (reaction to fire)
System 4 (applies to all other "Essential characteristics" in the table)

Harmonised standard EN 14496:2005

Notified body/ies Not relevant

European Assessment Document Not relevant

European Technical Assessment Not relevant

Technical Assessment Body Not relevant

Appropriate Technical Documentation and/or Specific Technical Documentation Not relevant

Declared performance/s

Essential characteristics	Performance	AVCP system	Harmonised technical specification
Reaction to fire	A1	CWFT	EN 14496:2005
Dangerous substances	NPD		EN 14496:2005
Bond strength	≥ 0,06 MPa		EN 14496:2005

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



23.01.2020
Sto SE & Co. KGaA D-79780 Stühlingen

Francisco Ramos / Head of Business Fields Facade and Interiors

Attachment: Safety Data Sheet

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstraße 1
D-79780 Stühlingen

01-0323-1

20

PROD4204 StoSilent Coll MW-G
gypsum-based adhesive

onto walls, ceilings, pillars, and separating walls in interiors

Reaction to fire	A1
Bond strength	$\geq 0,06$ MPa
Dangerous substances	NPD