



Declaration of Performance for the construction product

StoSilent Modular 230

Unique identification code of the product-type	PROD3622 StoSilent Modular 230 Ceiling membrane of suspended ceiling <i>See the container imprint for the batch number.</i>
Intended use/es	Inside of buildings
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 3 (reaction to fire) System 4 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 13964:2014
Notified body/ies	NB 0672
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	AVCP system	Harmonised technical specification
Reaction to fire	A2-s1, d0 Carrier board with coating	System 3	EN 13964:2014
Reaction to fire	C-s3, d0 Layer of PET fibre		EN 13964:2014
Release of dangerous substances	no release of asbestos		EN 13964:2014
Release of dangerous substances	formaldehyde class E1		EN 13964:2014
Sound absorption area A (object) / m ²	See test report M 100 960/26 of 18 December 2019 Müller BBM		EN 13964:2014

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



23.11.2020
Sto SE & Co. KGaA D-79780 Stühlingen

Francisco Ramos / Head of Business Fields Facade and Interiors

Attachment: Safety Data Sheet

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA

Ehrenbachstraße 1

D-79780 Stühlingen

01-0269-3

16

NB 0672

PROD3622 StoSilent Modular 230
EN 13964 Ceiling membrane of suspended ceiling

Inside of buildings

Reaction to fire	A2-s1, d0 Carrier board with coating
Reaction to fire	C-s3, d0 Layer of PET fibre
Release of dangerous substances	no release of asbestos
Release of dangerous substances	formaldehyde class E1
Sound absorption area A (object) / m ²	See test report M 100 960/26 of 18 December 2019 Müller BBM