

Declaration of Performance for the construction product StoTap Select C

Unique identification code of the product-type	PROD5107 StoTap Select C
Intended use/es	wall covering product covering for interior walls, separating walls, and ceilings
Manufacturer	Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen
System/s of AVCP	System 4 (reaction to fire) System 4 (applies to all other "Essential characteristics" in the table)
Harmonised standard	EN 15102:2007+A1:2011
Notified body/ies	Not relevant
European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment Body	Not relevant
Appropriate Technical Documentation and/or Specific Technical Documentation	Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	D-s3, d2	EN 15102:2007+A1:2011
Sound absorption coefficient α_w	NPD	EN 15102:2007+A1:2011
Formaldehyde release	passed (< 120 mg/kg)	EN 15102:2007+A1:2011
Dangerous substances: heavy metals and other elements	pass	EN 15102:2007+A1:2011
Dangerous substances: vinyl chloride monomer (VCM)	pass	EN 15102:2007+A1:2011
Thermal resistance	NPD	EN 15102:2007+A1:2011

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

09.07.2025

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA
Ehrenbachstr. 1
D-79780 Stühlingen

0101-0451-1

25

**PROD5107 StoTap Select C
EN 15102 wall covering product**

covering for interior walls, separating walls, and ceilings

Reaction to fire	D-s3, d2
Sound absorption coefficient α_w	NPD
Formaldehyde release	passed (< 120 mg/kg)
Dangerous substances: heavy metals and other elements	pass
Dangerous substances: vinyl chloride monomer (VCM)	pass
Thermal resistance	NPD