

# Declaration of Performance for the construction product Stolit® QS K

|                                                                                |                                                                                                         |
|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| Unique identification code of the product-type                                 | PROD0717 Stolit® QS K                                                                                   |
| Intended use/s                                                                 | render/plaster with organic binding agents<br>onto walls, ceilings and pillars in exteriors             |
| Manufacturer                                                                   | Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen                                                  |
| System/s of AVCP                                                               | System 3 (reaction to fire)<br>System 4 (applies to all other "Essential characteristics" in the table) |
| Harmonised standard                                                            | EN 15824:2017                                                                                           |
| Notified body/ies                                                              | MPA NRW NB 0432                                                                                         |
| European Assessment Document                                                   | Not relevant                                                                                            |
| European Technical Assessment                                                  | Not relevant                                                                                            |
| Technical Assessment Body                                                      | Not relevant                                                                                            |
| Appropriate Technical Documentation and/or<br>Specific Technical Documentation | Not relevant                                                                                            |

## Declared performance/s

| Essential characteristics | Performance | Harmonised technical specification |
|---------------------------|-------------|------------------------------------|
| Reaction to fire          | A2-s1, d0   | EN 15824:2017                      |
| Water absorption          | W 3         | EN 15824:2017                      |
| Water vapour permeability | V 2         | EN 15824:2017                      |
| Thermal conductivity      | NPD         | EN 15824:2017                      |
| Durability                | NPD         | EN 15824:2017                      |
| Dangerous substances      | NPD         | EN 15824:2017                      |
| Bond strength             | ≥ 0,3 MPa   | EN 15824:2017                      |

*NPD = no performance determined*

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppa Francisco Ramos / Head of Business Fields Facade and Interiors

This copy was created by machine and is valid without signature.

17.05.2024

Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

The current valid version of the declaration of performance is available at [www.sto.com/ce](http://www.sto.com/ce).

Sto SE & Co. KGaA  
Ehrenbachstr. 1  
D-79780 Stühlingen

Declaration of Performance 0101-0034-5  
In accordance with EU-CPR no. 305/2011



Sto SE & Co. KGaA  
Ehrenbachstr. 1  
D-79780 Stühlingen

0101-0034-5

10

NB 0432

**PROD0717 Stolit<sup>®</sup> QS K**  
**EN 15824:2017 render/plaster with organic binding agents**  
onto walls, ceilings and pillars in exteriors

|                           |           |
|---------------------------|-----------|
| Reaction to fire          | A2-s1, d0 |
| Water absorption          | W 3       |
| Thermal conductivity      | NPD       |
| Bond strength             | ≥ 0,3 MPa |
| Durability                | NPD       |
| Water vapour permeability | V 2       |
| Dangerous substances      | NPD       |