



StoPma GH 300

Sustainability

Data for building certification systems

Deutsche Gesellschaft für Nachhaltiges Bauen e.V. (German Sustainable Building Council, DGNB for short)		
ENV1.2, Version 2018	Product group:	No. 22: PMMA and PMMA / epoxy coatings for floor areas (and wall areas) with special requirements and liquid-applied bridge deck waterproofing
	Quality level:	meets quality level 4 – GISCODE RMA10 or RMA15
ENV1.2, Version 2023	Product group:	No. 22: PMMA and PMMA / epoxy coatings for floor areas and wall areas with special requirements and liquid-applied bridge deck waterproofing
	Quality level:	meets quality level 4 – GISCODE RMA10 or RMA15
ENV1.2, Version 2023	Product group:	no. 22: poly(methyl methacrylate) (PMMA) reactive resins, interior and exterior
	Quality level:	meets quality level 4 – GISCODE RMA10 or RMA15

Qualitätssiegel Nachhaltiges Gebäude (German Quality Label for Sustainable Building, QNG for short)		
Annex document 313 dated 14 September 2023	Product group:	No. 5.10: Synthetic resin screeds and PMMA coatings (including surface protection systems) for floor and wall areas, as well as PMMA liquid-applied bridge deck waterproofing (interior and exterior)
	Quality level:	Not relevant for inclusion, as exterior product
Proposal for assignment: LCA calculation values for QNG Sustainable Building Certification	8.24 Methacrylate resins	

Bewertungssystem Nachhaltiges Bauen (German Assessment System for Sustainable Building, BNB for short)		
BNB_BN 1.1.6, Version 2015	Product group:	No. 20b: PMMA liquid-applied bridge deck waterproofing coatings (including in combination) with special resistance requirements for floor, wall, and roof areas
	Quality level:	Meets quality level 5 – GISCODE RMA10

Minergie-ECO / ecobau

Minergie ECO classification	Minergie ECO specification 120-04 solvent emissions from building materials met
------------------------------------	---

Leadership in Energy and Environmental Design (LEED v. 4.1)

VOC content (EQ Credit: Low-emitting materials)	0 g/l (Without water) calculated according to the SCAQMD METHOD 304-91 (5.1) Met in accordance with LEED v4
--	---

VOC emissions (EQ Credit: Low-emitting materials)	Requirement:	Not relevant as exterior product
--	--------------	----------------------------------

SVOC emissions (EQ Credit: Low-emitting materials)	Requirement:	Not relevant as exterior product
---	--------------	----------------------------------

Formaldehyde emissions (EQ Credit: Low-emitting materials)	Requirement:	Not relevant as exterior product
---	--------------	----------------------------------

Recycling percentage (post-consumer recycled content) (MR Credit: Sourcing of raw materials)	0 %
---	-----

Recycling percentage (pre-consumer recycled content) (MR Credit: Sourcing of raw materials)	0 %
--	-----

Renewable raw materials (bio-based materials) (MR Credit: Sourcing of raw materials)	0 %
---	-----

Building Research Establishment Environmental Assessment Method (BREEAM)

VOC content (EQ Credit: Low-emitting materials)	0 g/l (Without water) calculated according to the SCAQMD METHOD 304-91 (5.1) Met in accordance with BREEAM
--	--

VOC emissions (Hea 02: indoor air quality)	Requirement:	Not relevant as exterior product
---	--------------	----------------------------------

SVOC emissions (Hea 02: indoor air quality)	Requirement:	Not relevant as exterior product
--	--------------	----------------------------------

Building Research Establishment Environmental Assessment Method (BREEAM)

Formaldehyde emissions (Hea 02: indoor air quality)	Requirement:	Not relevant as exterior product
CMR emissions (Hea 02: indoor air quality)	Requirement:	Not relevant as exterior product

EU Taxonomy Regulation (EU) 2020/852

Compliant with Annex C	Met	
Note	This statement is based on the formulation data of Sto SE & Co. KGaA and information from our upstream suppliers.	
Formaldehyde emissions	Requirement:	Not relevant as exterior product
Other carcinogenic VOCs in categories 1A and 1B (CMR)	Requirement:	Not relevant as exterior product
Compliant with minimum social requirements (human rights, German Supply Chain Due Diligence Act, etc.)	https://www.stocretec.de/s/unternehmen/compliance	

Eco-labels and environmental labels**Eco-label, certificates**

ISO certification 9001, 14001, 50001	https://www.stocretec.de/s/unternehmen/managementsysteme	
Environmental Product Declaration (EPD)	EPD-DBC20250265-IBP1-EN	
Product-specific working life (in accordance with BNB service life table)	Years:	40 years
	Application range:	exterior
Product-specific working life (in accordance with EPD)	Years:	> 50 years
	Application range:	exterior
GISCODE	See SDS (section 15)	

Product ingredients

Organic component (in accordance with natureplus / baubook)	>5%	
Hazardous substances (in accordance with EU regulations)	See SDS (section 3)	
CMR substances (VOC)	Cannot be determined (limit of quantification: 1 mg/kg) (in accordance with DIN EN ISO 17895)	
VOC content (in accordance with Directive 2004/42/CE)	0 g/l	
Solvent (in accordance with VdL Directive 01)	Content:	< 700 mg/kg solvent-free
	Base:	According to formulation evaluation
Plasticiser (in accordance with VdL Directive 01)	Content:	< 500 mg/kg Plasticiser-free
	Base:	According to formulation evaluation
Free formaldehyde (in accordance with VdL Directive 01)	Content:	< 2 mg/kg Formaldehyde-free
	Base:	According to formulation evaluation
Biocide(s), active substance(s) for protection of the coating (in accordance with Regulation (EU) No 528/2012)	Not present	
Biocide(s), active substance(s) for protection of the product during storage (in accordance with Regulation (EU) No 528/2012)	Not present	
Heavy metals	Not assessed	
Compliant with the emissions restrictions of the titanium dioxide industry (in accordance with Directive 2010/75/EU and 25th Ordinance for the Implementation of the Federal Immission Control Act)	Not applicable, as titanium dioxide is not present in the product	

SVHC in accordance with the REACH chemicals regulation (EC/1907/2006), Annex XIV	Content:	<0,1%
	Base:	According to formulation evaluation

Carbon footprint

A1-A3 (cradle to gate – manufacturing)	5.15 kg CO ₂ e / kg
A4 (transport from manufacturer to site)	0.047 kg CO ₂ e / kg
A1-C4 (cradle to grave – life cycle)	5.377 kg CO ₂ e / kg
D (Benefits and loads beyond the system boundary)	-0.058 kg CO ₂ e / kg
A1-D (cradle to cradle – life cycle including benefit)	5.319 kg CO ₂ e / kg

Disposal, reuse, recycling

Recycling of site residue	See SDS (section 13)
Recycling of dismantled building material	Can be reworked
	See Environmental Product Declaration (EPD)
Recycling of packaging material	Can be reused or recycled
	See https://www.stocretec.de/s/service-tools/entsorgung
Circular economy at StoCretec	https://www.stocretec.de/s/nachhaltigkeit/kreislaufwirtschaft

Corporate responsibility at StoCretec

Guiding principles, management of the company	StoCretec's vision is to be the technology leader in the sustainable design of living space tailored to human needs. Worldwide. For further information please visit: www.stocretec.de
UN Global Compact - membership	StoCretec is a member of the UN Global Compact and is committed to upholding ten universally acknowledged principles taken from the areas of human rights, labour standards, environmental protection, and anti-corruption. For further information please visit: www.unglobalcompact.org

Supplier code of conduct	https://www.stocretec.de/cepcom/stocretec/Dokumente/nachhaltigkeit/Compliance/Sto-Supplier-Code-of-Conduct_01_12_23_DE.pdf
---------------------------------	---

Notes

Version	07
Creation and use	The information and data contained in this sustainability data sheet is based on our knowledge and experience. The publication of a new sustainability data sheet invalidates all previous versions. Please observe the information in the Technical Data Sheet and Safety Data Sheet. The latest version is available on the Internet. Formulations are subject to change!