

Sustainability Data Sheet



StoPur IB 500

PUR coating, viscoplastic, low-emission

For product description see Technical Data Sheet (if available)

Information for building certifications in accordance with DGNB

Quality level (ENV1.2, in accordance with the criteria matrix, DGNB System Version 2018)

no 24: EP/polyurethane primer and coatings for floor and wall areas with special requirements: meets quality level 4GISCODE PU10 / PU40 / PU60 / RE05 / RE10 / RE20, or RE30

Quality level (ENV1.2, in accordance with the criteria matrix, DGNB System Version 2023)

no. 24: epoxy resin/rigid polyurethane foam primers (also mastic asphalt screed) and coatings for floor and wall areas with special requirements: meets quality level 4 – GISCODE PU10 / PU40 / PU60 / RE05 / RE10 / RE20, or RE30

Product-specific LCA values (ENV 1.1 and ENV 2.1)

in accordance with EPD

Product-specific life cycle (ECO1.1)

30 years in interior application (in accordance with BNB)

Impact on acoustic comfort (SOC1.3)

not assessed

Cleaning instructions (PRO1.5 and TEC1.5)

see Technical Data Sheet

Easy to recycle building material selection (TEC1.6)

can be reworked

Information for building certifications in accordance with LEED

VOC content (EQ Credit: Low-emitting materials)

7,5 g/l (without water) calculated according to the SCAQMD METHOD 304-91 (5.1)
Met in accordance with LEED v.4

VOC and SVOC emissions (EQ Credit: Low-emitting materials)

system test report
Met in accordance with LEED v.4

Formaldehyde emissions

system test report
Met in accordance with LEED v.4

Recyclable percentage (post-consumer recycled content) (MR Credit: Sourcing of raw materials)

0 %

Sustainability Data Sheet



StoPur IB 500

Recyclable percentage (pre-consumer recycled content) (MR Credit: Sourcing of raw materials)

0 %

Renewable raw materials (bio-based materials) (MR Credit: Sourcing of raw materials)

0 %

Information for building certifications in accordance with BREEAM

Formaldehyde (Hea 02: indoor air quality)

limit of quantification $\leq 0.01 \text{ mg/m}^3$ (excellent quality)
below the limit of quantification, see system test report

VOC content (Hea 02: indoor air quality)

see Safety Data Sheet (section 15)

VOC emissions (Hea 02: indoor air quality)

limit of quantification $\leq 0.3 \text{ mg/m}^3$ (excellent quality)
below the limit of quantification, see system test report

SVOC emissions (Hea 02: indoor air quality)

limit of quantification $\leq 0.1 \text{ mg/m}^3$ (excellent quality)
below the limit of quantification, see system test report

CMR substances (Hea 02: indoor air quality)

limit of quantification $\leq 0.001 \text{ mg/m}^3$ (excellent quality)
below the limit of quantification, see system test report

Eco-labels and environmental labels

Certificates, eco-label, environmental label

Minergie-ECO specifications A1.050 "Lösemittel-Emissionen aus Bau- und Hilfsstoffen" (solvent emissions from building materials and processing aids) met; ecoBasis certified in the system

TÜV PROFiCERT-product Interior PREMIUM

TÜV PROFiCERT-product Interior Standard

Environmental Product Declaration (EPD)



EPD-FEI-20220109-IBG1

GISCODE (in accordance with GISBAU)

PU40

Safety Data Sheet (SDS)

available

Sustainability Data Sheet



StoPur IB 500

Technical Data Sheet (TDS)	available
Product ingredients	
Composition	See Safety Data Sheet (section 3), see Environmental Product Declaration (EPD)
Organic component (in accordance with natureplus, baubook)	> 5 %
Hazardous substances (in accordance with EU regulations)	See Safety Data Sheet (section 3)
CMR substances (VOC)	present (in accordance with DIN EN ISO 17895)
VOC content (in accordance with Directive 2004/42/CE)	see Safety Data Sheet (section 15)
Plasticiser	plasticiser-free (materials in accordance with VdL guideline 01), (after formulation evaluation)
Free formaldehyde	not present (after formulation evaluation)
Biocide(s), active substance(s) for protection of the coating (in accordance with Regulation (EU) No 528/2012)	not present
Biocide(s), active substance(s) for protection of the product during storage (in accordance with Regulation (EU) No 528/2012)	not present
Heavy metals	not assessed
Compliance with the emissions restrictions of the titanium dioxide industry (in accordance with Directive 2010/75/EU and 25th Ordinance for the Implementation of the Federal Immission Control Act)	yes
SVHC in accordance with the chemicals regulation REACH (EG/1907/2006), notes XIV	not present

Sustainability Data Sheet



StoPur IB 500

Emissions, CO2 balance sheet

**Carbon dioxide value (manufacturing A1-A3)
(cradle-to-gate)**

0,88 kg CO2e / kg

Carbon dioxide value (life cycle A1-D)

3,43 kg CO2e / kg

Semi-volatile organic compounds SVOCs

see Environmental Product Declaration (EPD)

Disposal, re-use, recycling

Disposal of residue

see safety data sheet (section 13)

Disposal of dismantled building material

can be reworked,
refer to EPD chapter 2.14 and 2.15

Packaging, pails, films

The return of used packaging and its correct recycling is organised and certified in accordance with the statutory requirements with a regional disposal company.

Sto corporate responsibility

Guiding principles, management of the company

Sto's vision is to be the technology leader in the sustainable design of living space tailored to human needs. Worldwide. For further information please visit: www.sto.com

UN Global Compact - membership

Sto is a member of the UN Global Compact and is committed to upholding ten universally acknowledged principles taken from the areas of human rights, labour standards, environmental protection, and anti-corruption. For further information please visit: www.unglobalcompact.org

ILO fundamental conventions

Sto has committed itself to adhering to the ILO fundamental conventions at all of its locations.

Quality management, environmental management, energy management

Production location certified in accordance with DIN EN 9001, DIN EN 14001, and DIN EN 50001.

Supplier code of conduct

The Sto Supplier Code of Conduct is based on the principles of the UN Global Compact and the Sto Guiding Principles. Suppliers must adhere to these and

Sustainability Data Sheet

StoPur IB 500



are continuously evaluated.

This document aims to help you better assess the sustainability of our products. We consider sustainability to be a complex process that involves bringing together economic, ecological, and social criteria in order to satisfy the needs of current and future generations. Our products aim to contribute to this, while also meeting the requirements placed on them with respect to well-being, quality, and functionality. We regard sustainability as a process of continuous improvement, not one with an end result. With this in mind, we have defined the following core statements for our products:

1. Sto products make a contribution to key aspects of sustainability: e.g. climate protection, building, energy, and resource efficiency, protection and durability, health, and well-being.
2. All of the raw materials used in Sto products fulfil the functions for their application and are optimised with respect to their impact on the environment - based on the latest technology.
3. Sto products are produced in an energy and resource-efficient manner; renewable raw materials are used when appropriate and acceptable from an ecological, economical, and social perspective.
4. Sto evaluates and promotes the potential to dispose of, reuse, and recycle its products, taking technological and economical feasibility into account.

It is not just down to us to determine how the sustainability of our products is interpreted and evaluated - your opinions and decisions also play a role. The information listed here, which has the environment and health as its main focus, aims to assist you in this regard.

The information and data contained in this sustainability data sheet is based on our knowledge and experience. The publication of a new sustainability data sheet invalidates all previous versions. Please observe the information in the Technical Data Sheet and Safety Data Sheet. The latest version is available on the Internet.

StoCretec GmbH
Gutenbergstr. 6
D-65830 Kriftel

Tel.: +49 6192 401-104
Fax: +49 6192 401-105
stocretec@sto.com
www.stocretec.de