

Sustainability Data Sheet

StoSilco® QS MP



Silicone resin finishing render as free-style textured render with early rainproofing properties

For product description see Technical Data Sheet (if available)

Information for building certifications in accordance with DGNB

Quality level (ENV1.2, in accordance with the criteria matrix, DGNB System Version 2018)

no. 5: coating materials for mineral surfaces in exterior areas: meets quality level 4 - VOC content < 40 g/l (in accordance with Directive 2004/42/CE)

Quality level (ENV1.2, in accordance with the criteria matrix, DGNB System Version 2023)

no. 5: coating materials for mineral surfaces in exterior areas: meets quality level 4 – VOC content < 40 g/l (in accordance with Directive 2004/42/CE) / justify need to use film-protected products with UBA information sheets incorporated

Product-specific LCA values (ENV 1.1 and ENV 2.1)

in accordance with EPD

Product-specific life cycle (ECO1.1)

40 years in exterior application (in accordance with BNB)

Impact on acoustic comfort (SOC1.3)

not assessed

Cleaning instructions (PRO1.5 and TEC1.5)

see Technical Data Sheet

Easy to recycle building material selection (TEC1.6)

can be reworked

Information for building certifications in accordance with LEED

VOC content (EQ Credit: Low-emitting materials)

46,5 g/l (without water) calculated according to the SCAQMD METHOD 304-91 (5.1)
Met in accordance with LEED v.4

VOC and SVOC emissions (EQ Credit: Low-emitting materials)

not relevant, as exterior product

Formaldehyde emissions

not relevant, as exterior product

Recyclable percentage (post-consumer recycled content) (MR Credit: Sourcing of raw materials)

0 %

Recyclable percentage (pre-consumer recycled

0 %

Sustainability Data Sheet



StoSilco® QS MP

content) (MR Credit: Sourcing of raw materials)

Renewable raw materials (bio-based materials)
(MR Credit: Sourcing of raw materials)

0 %

Information for building certifications in accordance with BREEAM

Formaldehyde (Hea 02: indoor air quality)

not relevant, as exterior product

VOC content (Hea 02: indoor air quality)

see Safety Data Sheet (section 15)

VOC emissions (Hea 02: indoor air quality)

not relevant, as exterior product

SVOC emissions (Hea 02: indoor air quality)

not relevant, as exterior product

CMR substances (Hea 02: indoor air quality)

not relevant, as exterior product

Eco-labels and environmental labels

Certificates, eco-label, environmental label

None

Environmental Product Declaration (EPD)



NEPD-12371-12400

GISCODE (in accordance with GISBAU)

BSW50

Safety Data Sheet (SDS)

available

Technical Data Sheet (TDS)

available

Product ingredients

Composition

In accordance with the VdL directive (German Paint and Printing Ink Association) on coating materials for buildings
Polymer dispersion
silicone resin emulsion
titanium dioxide
mineral extenders

Sustainability Data Sheet

StoSilco® QS MP



	aluminium hydroxide silicate extenders Water Glycol ether aliphatics Hydrophobic agents surface additive Thickener dispersing agent wetting agents coating protection agent based on terbutryn / OIT / ZPT
Organic component (in accordance with natureplus, baubook)	> 5 %
Hazardous substances (in accordance with EU regulations)	See Safety Data Sheet (section 3)
CMR substances (VOC)	present (in accordance with DIN EN ISO 17895)
VOC content (in accordance with Directive 2004/42/CE)	not subject to the guideline
Plasticiser	plasticiser-free (materials in accordance with VdL guideline 01), (according to measurement)
Free formaldehyde	≤ 10 mg/kg (MQuant® formaldehyde test according to the VdL guideline 03)
Biocide(s), active substance(s) for protection of the coating (in accordance with Regulation (EU) No 528/2012)	present, see Safety Data Sheet (section 2)
Biocide(s), active substance(s) for protection of the product during storage (in accordance with Regulation (EU) No 528/2012)	present, see Safety Data Sheet (section 2)
Heavy metals	not assessed
Compliance with the emissions restrictions of the titanium dioxide industry (in accordance with Directive 2010/75/EU and 25th Ordinance for the Implementation of the Federal Immission Control Act)	yes

Sustainability Data Sheet



StoSilco[®] QS MP

SVHC in accordance with the chemicals regulation REACH (EG/1907/2006), notes XIV

not present

Emissions, CO2 balance sheet

Carbon dioxide value (manufacturing A1-A3) (cradle-to-gate)

0,67 kg CO2e / kg

Carbon dioxide value (life cycle A1-D)

0,78 kg CO2e / kg

Semi-volatile organic compounds SVOCs

see Environmental Product Declaration (EPD)

Disposal, re-use, recycling

Disposal of residue

correctly sorted, clean material can be recycled
see Safety Data Sheet (section 13)

Disposal of dismantled building material

can be reworked or recycled as building materials,
refer to EPD chapter 2.14 and 2.15

Packaging, pails, films

The return of used packaging and its correct recycling is organised and certified in accordance with the statutory requirements with a regional disposal company.

Sto corporate responsibility

Guiding principles, management of the company

Sto's vision is to be the technology leader in the sustainable design of living space tailored to human needs. Worldwide. For further information please visit: www.sto.com

UN Global Compact - membership

Sto is a member of the UN Global Compact and is committed to upholding ten universally acknowledged principles taken from the areas of human rights, labour standards, environmental protection, and anti-corruption. For further information please visit: www.unglobalcompact.org

ILO fundamental conventions

Sto has committed itself to adhering to the ILO fundamental conventions at all of its locations.

Quality management, environmental management, energy management

Production location certified in accordance with DIN EN 9001, DIN EN 14001, and DIN EN 50001.

Sustainability Data Sheet

StoSilco® QS MP



Supplier code of conduct

The Sto Supplier Code of Conduct is based on the principles of the UN Global Compact and the Sto Guiding Principles. Suppliers must adhere to these and are continuously evaluated.

This document aims to help you better assess the sustainability of our products. We consider sustainability to be a complex process that involves bringing together economic, ecological, and social criteria in order to satisfy the needs of current and future generations. Our products aim to contribute to this, while also meeting the requirements placed on them with respect to well-being, quality, and functionality. We regard sustainability as a process of continuous improvement, not one with an end result. With this in mind, we have defined the following core statements for our products:

1. Sto products make a contribution to key aspects of sustainability: e.g. climate protection, building, energy, and resource efficiency, protection and durability, health, and well-being.
2. All of the raw materials used in Sto products fulfil the functions for their application and are optimised with respect to their impact on the environment - based on the latest technology.
3. Sto products are produced in an energy and resource-efficient manner; renewable raw materials are used when appropriate and acceptable from an ecological, economical, and social perspective.
4. Sto evaluates and promotes the potential to dispose of, reuse, and recycle its products, taking technological and economical feasibility into account.

It is not just down to us to determine how the sustainability of our products is interpreted and evaluated - your opinions and decisions also play a role. The information listed here, which has the environment and health as its main focus, aims to assist you in this regard.

The information and data contained in this sustainability data sheet is based on our knowledge and experience. The publication of a new sustainability data sheet invalidates all previous versions. Please observe the information in the Technical Data Sheet and Safety Data Sheet. The latest version is available on the Internet.

Sto SE & Co. KGaA
Ehrenbachstr. 1
D - 79780 Stühlingen
Phone: 07744 57-0
infoservice@sto.com
www.sto.de