

Technical Data Sheet

Sto-Aggregate KS

Aggregate mixture for scratch coats



Characteristics

Area of application • as a special aggregate for levelling coats

Information/notes • as an aggregate mixture for permanent vapour barriers

Application

Material consumption depends on the application, substrate, and consistency, among other factors. The stated consumption values are only to be used as a guide. If required, determine precise consumption values on the basis of the specific project.

Notes, recommendations, special information, miscellaneous Suitable mixing ratios for using Sto Zuschlag KS are described in the Technical Data Sheets of StoCretec priming resins (e.g. StoPox GH 205).

Delivery

Colour shade black

Packaging sack

Article number	Name	Container
14221-003	Sto Aggregate KS	25 kg bag

Identification

Special notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use. Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on the Internet.

Technical Data Sheet

Sto-Aggregate KS

StoCretec GmbH
Gutenbergstr. 6
D-65830 Kriftel

Tel.: +49 6192 401-104
Fax: +49 6192 401-105
stocretec@sto.com
www.stocretec.de