Technical Data Sheet
StoDivers LB 100

Conductive copper tape, tin-plated



Characteristics

Area of application
- for connecting electrically conductive floor coatings to the grounding system

Properties
- self-adhesive

Format
- width: 12 mm
- length: 16.5 m

Application

Consumption

Type	Approx. consumption
loose, width: 12 mm, length: 16.5 m	

Material consumption depends on the application, substrate, and consistency, among other factors. The stated consumption values are only to be used as a guide. If required, determine precise consumption values on the basis of the specific project.

Application

Delivery

Article number	Name	Container
03044-002	StoDivers LB 100	1 piece

Identification

Special notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use.
Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

Technical Data Sheet

StoDivers LB 100

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on the Internet.

StoCretec GmbH
Gutenbergstr. 6
D-65830 Kriftel

Tel.: +49 6192 401-104
Fax: +49 6192 401-105
stocretec@sto.com
www.stocretec.de