Technical Data Sheet

StoDivers LS

Conducting set

Characteristics

Area of application	• for electrically conductive epoxy resin textured sealing coats • connection to ground for electrically conductive floor coatings
Properties	• contains 10 connections
Information/notes	• only an electrician is permitted to make the connections to ground

Application

Consumption

Type	Approx. consumption	
box with 10 connections	1	pcs./pcs.

Material consumption depends on the application, substrate, and consistency, among other factors. The stated consumption values are only to be used as a guide. If required, determine precise consumption values on the basis of the specific project.

Delivery

Article number	Name	Container
03022-001	StoDivers LS	1 piece

Identification

Special notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use.
Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on the Internet.

Technical Data Sheet

StoDivers LS

StoCretec GmbH
Gutenbergstr. 6
D-65830 Kriftel

Tel.: +49 6192 401-104
Fax: +49 6192 401-105
stocretec@sto.com
www.stocretec.de