

Technical Data Sheet

StoQuarz RF

Quartz sand mixture for filling EP and PUR floor coatings, with an individually matched grain size distribution



Characteristics

Area of application • as an admixture for EP/PUR resins in accordance with the Technical Data Sheet

Properties • higher filling degrees possible than with conventional quartz sand mixtures
• lower settling tendency than with conventional quartz sand mixtures

Application

Application add to the total mixture

Delivery

Packaging sack

Article number	Name	Container
00554-002	StoQuarz RF	25 kg bag

Identification

Special notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use. Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on the Internet.

StoCretec GmbH
Gutenbergstr. 6
D-65830 Kriftel

Tel.: +49 6192 401-104

Technical Data Sheet

StoQuarz RF

Fax: +49 6192 401-105
stocretec@sto.com
www.stocretec.de