

Technical Data Sheet

Sto Ballotini Ø 250-425 µm

Solid glass beads for slip resistance Ø 250-425 µm



Characteristics

Area of application	<ul style="list-style-type: none"> as an admixture to StoPox or StoPur products in accordance with the relevant Technical Data Sheet
Properties	<ul style="list-style-type: none"> transparent solid glass beads as extenders to achieve slip-resistant sealed surfaces
Appearance	<ul style="list-style-type: none"> transparent

Application

Application	texture using a texturing roller, manually, add to the total mixture, apply with a plastic trowel
--------------------	---

Delivery

Packaging	sack
------------------	------

Article number	Name	Container
14252-001	Sto Ballotini 250-425 µm	25 kg bag

Identification

Special notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use. Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on the Internet.

Technical Data Sheet

Sto Ballotini Ø 250-425 µm

StoCretec GmbH
Gutenbergstr. 6
D-65830 Kriftel

Tel.: +49 6192 401-104
Fax: +49 6192 401-105
stocretec@sto.com
www.stocretec.de